



Catalog Number	12238
UPC Number	60198612238
Description	Heat Shrinkable Ring Terminals 12-10 AWG



Features


Color Coded HD Polyethylene Heat Shrink insulation
Manufactured from high strength copper alloy
Electro-tin plated for corrosion resistance
Expanded Insulation funnel entry eliminates strand “Hang Up”, increases the crimping rates and the reliability of the termination
Wire range stamped on the surface for easy interpretation
Brazed seam prevent splitting under maximum pressure
Serrated barrel & flared position of sleeve provides excellent contact & mechanical stress relief at insulation & barrel junction

General

Insulation Type	High Density Polyethylene Heat Shrink
Material	Copper
Finish	Electro-tin plated
Color	Yellow
Wire Range	12-10 AWG
Stud Size	#8

Dimension Information

L Inches (mm)	1.339
W Inches (mm)	0.374
d2 Inches (mm)	0.169
T Inches (mm)	0.039



Specifications

Temperature Rating	105°C
Voltage Rating	600 V
Flammability Rating	UL94V-O
Amp Rating	12 AWG 35 Amps
	10 AWG 50 Amps

Packaging

Bag Qty	100
Master Bag Qty	1000

Certifications

UL	Yes
cUL	Yes
RoHS	Yes

Morris Products 53 Carey Road, Queensbury, NY 12804

www.morrisproducts.com