



LED EXIT SIGNS



Exit Signs

- Compact, Low Profile Design in Neutral Finish
- Push to Test Switch in Battery Backup Units
- Automatic, Low Voltage Disconnect (LVD)
- 120 or 277 VAC Operation
- Models 73022 - 73025 have Remote Capability for up to 2 Additional LED Remote Lamp Heads
2 heads - 3 hours operation (Base Unit)
3 heads - 2 hours operation (Base Unit + 1 Head)
4 heads - 1.5 hours operation (Base Unit + 2 Heads)
- Injection-Molded, UL 94 V-0 Flame Retardant, High Impact Thermoplastic Housing
- 2.4V 400mAh Ni-Cad Battery On Standard Units
- 3.6V 1800mAh Ni-Ni-Cad Battery On High Output & Remote Capable Units
- 90 Minute Battery Run Time
- UL 924 Listed for damp locations
- 3 Year Warranty
- See Pg 11 for Remote Lamp Heads

CAT. NO.	LED COLOR	HOUSING COLOR	VOLTS	BATTERY BACKUP	CASE QTY
STANDARD					
73010	RED	WHITE	120/277V	NO	6
73012	RED	WHITE	120/277V	YES	6
73013	RED	BLACK	120/277V	YES	6
73014	GREEN	WHITE	120/277V	NO	6
73016	GREEN	WHITE	120/277V	YES	6
73017	GREEN	BLACK	120/277V	YES	6
REMOTE CAPABLE (USE ONLY 3.6V LED REMOTE HEADS)					
73022	RED	WHITE	120/277V	YES	6
73024	GREEN	WHITE	120/277V	YES	6
73025	GREEN	BLACK	120/277V	YES	6
2 CIRCUIT UNIT WIRED FOR AC POWER & DC GENERATOR BACKUP					
73026	RED	WHITE	120/277V	NO	6
73028	GREEN	WHITE	120/277V	NO	6
STANDARD WITH SELF DIAGNOSTIC					
73512	RED	WHITE	120/277V	YES	6
73514	GREEN	WHITE	120/277V	YES	6
REMOTE CAPABLE WITH SELF DIAGNOSTIC (USE ONLY 3.6V LED REMOTE HEADS) (WILL NOT OPERATE CORRECTLY UNLESS USED WITH REMOTE HEADS)					
73516*	RED	WHITE	120/277V	YES	6
73518*	GREEN	WHITE	120/277V	YES	6

* Self Diagnostic Feature continually diagnoses unit performance and tests system to ensure reliable operation and to meet electrical & Life Safety Codes