



OUTDOOR COLD WEATHER WET LOCATION LED EMERGENCY



REMOTE CAPABLE

Remote Capability for up to 2 Additional LED Remote Lamp Heads (Use Only 3.6V LED Remote Heads)

- 2 heads - 3 hours operation (Base Unit)
- 3 heads - 2 hours operation (Base Unit + 1 Head)
- 4 heads - 1.5 hours operation (Base Unit + 2 Heads)

USE ONLY WITH 3.6V LED REMOTE LAMP HEADS

- Flame Retardant, UV-stabilized Polycarbonate Gasketed Housing, Integral Breather Vent & External Mounting Brackets
- 9.6V 1900mah maintenance-free, rechargeable Ni-Cad Battery
- Internal Solid-State Transfer Switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination
- Dual 120/277 voltage
- Sealed and Gasketed Weatherproof Lamp Heads with chrome reflector and tempered glass lens
- Top and side KD's provided for conduit feed applications
- Meets UL924 for Wet Locations, NFPA 101 Life Safety Code, NEC, OSHA
- Operating Temperature -4°F to +122°F
- 3 Year Warranty
- See Pg 11 for remote lamp heads



CAT. NO.	HOUSING	VOLTS	BATTERY	CASE QTY
73370	POLY-CARBONATE	120/277V	9.6V 1900 MAH NI-CAD	4

INDOOR LED EMERGENCY LIGHTS WET LOCATION



- This enclosure is ideal for wet locations, resistant to corrosive atmospheres, non-hazardous dust environments, water spray or splashing water
- Dual 120 or 277 VAC input, field selectable
- Solid-state line-latched low voltage disconnect provides 100% load disconnect protection to guard against battery deep discharge
- Tempered Glass Lens
- 6V Lead Acid Battery
- Meets UL924 for Wet Locations, NFPA 101 Life Safety Code, NEC, OSHA
- 3 Year Warranty



CAT. NO.	VOLTS	BATTERY	CASE QTY
73396A	120/277V	NICKEL CADMIUM	4

INDOOR LED COMBO EXIT/EMERGENCY LIGHT WET LOCATION



- Flame Retardant, UV-stabilized Corrosion & Impact Resistant Polycarbonate Housing with Clear Polycarbonate Cover
- Enclosure Resistant to Corrosive Atmospheres, Non-Hazardous Dust Environment, Hose-Down Water Spray or Splashing Water
- Universal Canopy Mount & 2 Face Plates for Side or Top Installation
- NiCad or Ni-MH battery Backup
- Input Voltage: 120/277
- 3 Year Warranty
- See Pg 11 for remote lamp heads



CAT. NO.	LED COLOR	VOLTS	BATTERY	LENGTH	DEPTH	HEIGHT	CASE QTY
STANDARD EXIT SIGN							
73452	RED	120/277V	2.4V 500MAH NI-CD	12-5/8"	2-1/2"	8-1/8"	4
73453	GREEN	120/277V	2.4V 500MAH NI-CD	12-5/8"	2-1/2"	8-1/8"	4
REMOTE CAPABLE EXIT SIGN							
73454	RED	120/277V	3.6V 1800MAH NI-MH	12-5/8"	2-1/2"	8-1/8"	4
73455	GREEN	120/277V	3.6V 1800MAH NI-MH	12-5/8"	2-1/2"	8-1/8"	4
STANDARD COMBO HIGH OUTPUT							
73456	RED	120/277V	3.6V 1000MAH NI-CD	12-9/16"	2-1/2"	13-5/16"	4
73457	GREEN	120/277V	3.6V 1000MAH NI-CD	12-9/16"	2-1/2"	13-5/16"	4
REMOTE CAPABLE COMBO HIGH OUTPUT							
73458	RED	120/277V	3.6V 1800MAH NI-MH	12-9/16"	2-1/2"	13-5/16"	4

Models 73454/73055 & 73458 - Remote Capability for up to 2 Additional LED Remote Lamp Heads. See Cat Pg 11

- 2 heads - 3 hours operation (Base Unit)
- 3 heads - 2 hours operation (Base Unit + 1 Head)
- 4 heads - 1.5 hours operation (Base Unit + 2 Heads)