



Catalog Number 20710A-20790A-Spec
UPC Number
Description Natural Nylon Cable Ties
Stainless Steel Locking Pawl

Features

- Cable ties are made from UL approved Nylon 6/6
- Bent Ribbed Tip design provides Proper Orientation to locking head and Superior Grip for ease of insertion
- Concave Tip design achieves extremely Low Insertion Force characteristics
- Hardened Stainless Steel internal Locking Pawl ensures Superior Tensile Strength Positive Lock and Reliable Performance
- Normal service temperature range -40° to 185°F(-40° to 85°C)
- Flammability Rating UL94V-2

General

Material: Natural Nylon 6/6
Material Pawl: Hardened Stainless Steel
45° Pitch/60° Cutting Angle
Color: White

Dimension Information

Length Inches: See Table
Width Inches: See Table
Thickness Inches: See Table
Tensile Strength: See Table

Specifications

Temperature Rating -40° to 185°F(-40° to 85°C)
Voltage Rating N/A
Flammability Rating UL94V-2

Packaging

Bag Qty See Table

Certifications

UL Yes
cUL
RoHS Yes





Natural - Stainless Steel Pawl

DIMENSIONS = INCHES

CAT. NO.	TENSILE STRENGTH (LBS.)	LENGTH	WIDTH	MAX BUNDLE DIA.	BAG QTY
20710A	18	4"	.098	0.94	100
20710B	18	4"	.098	0.94	1,000
20712	40	4"	.140	0.94	100
20713A	40	6"	.140	1.40	100
20713B	40	6"	.140	1.40	1,000
20714A	40	8"	.140	2.16	100
20718A	50	8"	.180	2.16	100
20718B	50	8"	.180	2.16	1,000
20719A	50	10"	.180	2.75	100
20720A	50	12"	.180	3.25	100
20720B	50	12"	.180	3.25	1,000
20722	88	8"	.180	2.16	100
20724	88	11"	.180	3.19	100
20726	88	14"	.180	3.90	100
20750A	120	11"	.390	3.19	100
20752A	120	14"	.390	3.90	100
20754A	120	17"	.390	5.00	100
20756A	120	21"	.390	6.26	100
20758A	120	24"	.390	7.00	100
20760A	175	8"	.299	2.16	50
20762A	175	11"	.299	3.19	50
20728	175	14"	.299	3.90	50
20764A	175	17"	.299	5.00	50

Ultraviolet Black - Stainless Steel Pawl

DIMENSIONS = INCHES

CAT. NO.	TENSILE STRENGTH (LBS.)	LENGTH	WIDTH	MAX BUNDLE DIA.	BAG QTY
20730A	18	4	.098	0.94	100
20730B	18	4	.098	0.94	1,000
20732	40	4	.140	0.94	100
20733A	40	6	.140	1.40	100
20733B	40	6	.140	1.40	1,000
20734A	40	8	.140	2.16	100
20738A	50	8	.180	2.16	100
20738B	50	8	.180	2.16	1,000
20739A	50	10	.180	2.75	100
20740A	50	12	.180	3.25	100
20740B	50	12	.180	3.25	1,000
20742	88	8	.180	2.16	100
20744	88	11	.180	3.19	100
20746	88	14	.180	3.90	100
20776A	120	11	.390	3.19	100
20778A	120	14	.390	3.90	100
20780A	120	17	.390	5.00	100
20782A	120	21	.390	6.26	100
20784A	120	24	.390	7.00	100
20786A	175	8	.299	2.16	50
20788A	175	11	.299	3.19	50
20748	175	14	.299	3.90	50
20790A	175	17	.299	5.00	50