




Catalog Number 23054 - 23556
UPC Number
Description Winged Wire Connectors



Features

- Plastic Housing molded with strong, durable UL94V-2 flame retardant Nylon 6/6
- Swept-back wings designed to provide ergonomic grip, low torque & ease of termination
- Compact design perfect for tight spaces
- Color coded to industry standard
- 600V, 1000 Volts Max. in lighting fixtures and signs

General

Material: Polyimide Nylon 6/6
 Spring Steel Wire Core

Dimension Information

See Engineering Dwg

Specifications

Flammability Rating: UL 94V-2
Temperature Rating: 105°C
Voltage Rating: 600V 1000V Lighting Fixtures & Signage

Packaging

Bag Qty See Table

Certifications

UL UL 486C
CSA CSA 22.2 #188
ROHS Yes

No.	Color	Wire Combinations	A	B	C	D	E	Qty	Case Qty
Hanging Bag 25 Pack									
23254	Yellow	Max: 3 #12 Min: 4 #22	0.287	0.429	0.492	0.417	0.992	25	1250
23256	Red	Max: 1 #8 w/3 #12 str. Min: 3#20	0.358	0.520	0.583	0.453	1.161	25	1250
Boxed 100 Pack									
23054	Yellow	Max: 3 #12 Min: 4 #22	0.287	0.429	0.492	0.417	0.992	100	6000
23056	Red	Max: 1 #8 w/3 #12 str. Min: 3#20	0.358	0.520	0.583	0.453	1.161	100	4800
Bulk 500 Pack									
23154	Yellow	Max: 3 #12 Min: 4 #22	0.287	0.429	0.492	0.417	0.992	500	5000
23156	Red	Max: 1 #8 w/3 #12 str. Min: 3#20	0.358	0.520	0.583	0.453	1.161	500	5000
Small Jar									
23354	Yellow	Max: 3 #12 Min: 4 #22	0.287	0.429	0.492	0.417	0.992	250	8000
23356	Red	Max: 1 #8 w/3 #12 str. Min: 3#20	0.358	0.520	0.583	0.453	1.161	100	3200
Large Jar									
23454	Yellow	Max: 3 #12 Min: 4 #22	0.287	0.429	0.492	0.417	0.992	600	7200
23456	Red	Max: 1 #8 w/3 #12 str. Min: 3#20	0.358	0.520	0.583	0.453	1.161	400	4800
Handy Pack									
23554	Yellow	Max: 3 #12 Min: 4 #22	0.287	0.429	0.492	0.417	0.992	250	4000
23556	Red	Max: 1 #8 w/3 #12 str. Min: 3#20	0.358	0.520	0.583	0.453	1.161	170	2720