



Catalog Number 23071 - 23576
UPC Number
Description Wire Connectors



- Features**
- Five color-coded screw on wire connectors cover a full range of wire sizes from 22 through 8 Awg
 - Ribbed-Cap provides a more secure grip and faster fingertip starts even when hands become slippery
 - Temperature rated at 221°F (105°C) maximum
 - No pre-twisting of conductors is required – spring creates its own thread
 - Reusable screw on wire connector threads on or off splice for fast and easy circuit changes and additions
 - Tough, UL 94V-2 Flame retardant shell will not crack or break, even when applied to maximum wire combinations under extreme pressure


General
 Material: Heavy Duty Thermoplastic
 Spring Steel Wire Core

Dimension Information
 See Engineering Dwg

Specifications
 Flammability Rating: UL 94V-2
 Temperature Rating: 212°F (105°C)
 Voltage Rating: 600V 1000V Lighting Fixtures & Signage

Packaging
 Bag Qty See Table

Certifications
 UL UL 486C
 cULus cULus
 ROHS Yes





Cat No	Packaging	Type	Color	Wire Combinations	Max Volts	A	B	C	D	E
23271	25 Pack	P1	Gray	Max: 1 #14 w/1 #20 Min: 2 #22	300V	0.15	0.264	0.339	0.228	0.598
23272	25 Pack	P2	Blue	Max: 3 #16 Min: 2 #22	300V	0.161	0.276	0.386	0.232	0.693
23273	25 Pack	P3	Orange	Max: 4 #16 w/1 #20 Min: 1 #18 w/1 #20	600V	0.197	0.39	0.48	0.307	0.862
23274	25 Pack	P4	Yellow	Max: 1 #10 w/2#14 w/1 #16 Min: 3 #20	600V	0.236	0.441	0.551	0.311	0.937
23276	25 Pack	P6	Red	Max: 3 #10 Min: 3 #18	600V, 1000V	0.276	0.504	0.63	0.35	1.047
23071	Boxed 100	P1	Gray	Max: 1 #14 w/1 #20 Min: 2 #22	300V	0.15	0.264	0.339	0.228	0.598
23072	Boxed 100	P2	Blue	Max: 3 #16 Min: 2 #22	300V	0.161	0.276	0.386	0.232	0.693
23073	Boxed 100	P3	Orange	Max: 4 #16 w/1 #20 Min: 1 #18 w/1 #20	600V	0.197	0.39	0.48	0.307	0.862
23074	Boxed 100	P4	Yellow	Max: 1 #10 w/2#14 w/1 #16 Min: 3 #20	600V	0.236	0.441	0.551	0.311	0.937
23076	Boxed 100	P6	Red	Max: 3 #10 Min: 3 #18	600V, 1000V	0.276	0.504	0.63	0.35	1.047
23171	Bagged Bulk	P1	Gray	Max: 1 #14 w/1 #20 Min: 2 #22	300V	0.15	0.264	0.339	0.228	0.598
23172	Bagged Bulk	P2	Blue	Max: 3 #16 Min: 2 #22	300V	0.161	0.276	0.386	0.232	0.693
23173	Bagged Bulk	P3	Orange	Max: 4 #16 w/1 #20 Min: 1 #18 w/1 #20	600V	0.197	0.39	0.48	0.307	0.862
23174	Bagged Bulk	P4	Yellow	Max: 1 #10 w/2#14 w/1 #16 Min: 3 #20	600V	0.236	0.441	0.551	0.311	0.937
23176	Bagged Bulk	P6	Red	Max: 3 #10 Min: 3 #18	600V, 1000V	0.276	0.504	0.63	0.35	1.047
23373	Small Jar	P3	Orange	Max: 4 #16 w/1 #20 Min: 1 #18 w/1 #20	600V	0.197	0.39	0.48	0.307	0.862
23374	Small Jar	P4	Yellow	Max: 1 #10 w/2#14 w/1 #16 Min: 3 #20	600V	0.236	0.441	0.551	0.311	0.937
23376	Small Jar	P6	Red	Max: 3 #10 Min: 3 #18	600V, 1000V	0.276	0.504	0.63	0.35	1.047
23473	Large Jar	P3	Orange	Max: 4 #16 w/1 #20 Min: 1 #18 w/1 #20	600V	0.197	0.39	0.48	0.307	0.862
23474	Large Jar	P4	Yellow	Max: 1 #10 w/2#14 w/1 #16 Min: 3 #20	600V	0.236	0.441	0.551	0.311	0.937
23476	Large Jar	P6	Red	Max: 3 #10 Min: 3 #18	600V, 1000V	0.276	0.504	0.63	0.35	1.047
23573	Handy Pack	P3	Orange	Max: 4 #16 w/1 #20 Min: 1 #18 w/1 #20	600V	0.197	0.39	0.48	0.307	0.862
23574	Handy Pack	P4	Yellow	Max: 1 #10 w/2#14 w/1 #16 Min: 3 #20	600V	0.236	0.441	0.551	0.311	0.937
23576	Handy Pack	P6	Red	Max: 3 #10 Min: 3 #18	600V, 1000V	0.276	0.504	0.63	0.35	1.047