



Catalog Number 23161 - 23163
UPC Number
Description High Temperature Wire Connectors

Features

- High Temperature Connector for high heat applications
- Ribbed-Cap provides a more secure grip and faster fingertip starts even when hands become slippery
- Temperature rated at 302°F (150°C) maximum
- No pre-twisting of conductors is required – spring creates its own thread
- Reusable connector threads on or off splice for fast and easy circuit changes and additions
- Tough, UL 94V-2 Flame retardant shell will not crack or break, even when applied to maximum wire combinations under extreme pressure

General

Material: Heavy Duty Thermoplastic
 Spring Steel Wire Core

Dimension Information

See Engineering Dwg

Specifications

Flammability Rating: UL 94V-2
Temperature Rating: 150°C
Voltage Rating: 600V 1000V Lighting Fixtures & Signage

Packaging

Bag Qty See Table

Certifications

UL UL 486C
CSA CSA 22.2 #188
ROHS Yes

No.	Type	Wire Combinations	Max Volts	A	B	C	D	E	Bag Qty	Case Box	
23161	P1	No.22 Thru 16 Awg	300V	0.15	0.264	0.339	0.228	0.598	100	20,000	
23163	P3	No.22 Thru 14 Awg	600V 1000V fixtures & Signs	0.197	0.390	0.480	0.307	0.866	100	5000	

www.morrisproducts.com

Morris Products 53 Carey Road, Queensbury, NY 12804