



Features:

Heavy Wall Heat Shrink Tubing features include:

- 3:1 Shrink Ratio
- High voltage heat shrink tubing provides maximum reliability for insulating and protection of cable joints and terminations
- Withstands severe mechanical requirements of U.R.D., submersible and direct burial installations
- High impact, abrasion, corrosion and chemical resistance
- Rated for 1000V
- 4' Lengths and Rolls have Thermoplastic Adhesive Liner provides complete environmental protection and insulation
- Heat shrink tubing meets: UL 486D, CSA C22.2 No. 198.2, ANSI C119.1, Western Underground Guide Numbers 2.4, 2.5, ICEA and NEMA insulation thickness requirements
- Provides Complete Environmental Protection
- Continuous operating temperature: -67°F to 230°F (-55°C to 110°C)
- Shrink temperature: 248°F (120°C)
- Heavy Wall holds better mechanically & has better underground protection than medium wall
- Black color
- Order Qty of 1 = 1 Piece

DIMENSIONS = INCHES

CAT. NO.	CABLE RANGE	LENGTH	DIAMETER BEFORE SHRINKING	DIAMETER AFTER SHRINKING	WALL THICKNESS
68162	#14-#10	4 FT	0.35	0.12	.07
68164	#8-#6	4 FT	0.51	0.16	.09
68166	#6-#2	4 FT	0.75	0.24	.09
68168	#1-#3/0	4 FT	1.10	0.35	.12
68170	2/0-350	4 FT	1.50	0.47	.16
68172	250-500	4 FT	2.00	0.63	.16
68174	600-1000	4 FT	2.70	0.87	.16
68176	800-1250	4 FT	3.54	1.18	.16
68178	1500-2500	4 FT	4.72	1.57	.17
ROLLS					
68182	#14-#10	25 FT	0.35	0.12	.07
68186	#6-#2	25 FT	0.75	0.24	.09
68188	#1-#3/0	25 FT	1.10	0.35	.12
68190	2/0-350	25 FT	1.50	0.47	.16
68192	250-500	25 FT	2.00	0.63	.16
68194	600-1000	25 FT	2.70	0.87	.16
68196	800-1250	25 FT	3.54	1.18	.16