



MORRIS CAT#: 68320  
Thin Wall Heat Shrink Tubing Kits - Colors



68320

**Features:**

Thin Wall Heat Shrink Tubing In Kits Colors features include:

- Heat Shrink Tubing used for Electrical Insulation, Wire Harness, Bundling, Splices & Terminations
- Pre-Cut Flexible Polyolefin Tubing
- 2:1 Shrink Ratio
- Rated for 600 Volt 257°F (125°C) Continuous Operation
- Heat Shrink Tubing forms tough, smooth insulated covering resistant to common fluids and solvents
- Kit Contents:
  - Length: 1.375" Qty: 5 Ea Red, Blue, White, Yellow Dia. Before Shrink: .078" Dia. After Shrink: .029"
  - Length: 1.375" Qty: 5 Ea Red, Blue, White, Yellow Dia. Before Shrink: .098" Dia. After Shrink: .039"
  - Length: 1.375" Qty: 5 Ea Red, Blue, White, Yellow Dia. Before Shrink: .137" Dia. After Shrink: .059"
  - Length: 1.375" Qty: 5 Ea Red, Blue, White, Yellow Dia. Before Shrink: .212" Dia. After Shrink: .098"
  - Length: 2.953" Qty: 3 Red, 2 Blue, 3 White, 2 Yellow Dia. Before Shrink: .251" Dia. After Shrink: .117"
  - Length: 2.953" Qty: 1 Red, 2 Blue, 1 White, 1 Yellow Dia. Before Shrink: .370" Dia. After Shrink: .176"
  - Length: 2.953" Qty: 1 Red, 2 Blue, 1 White, 1 Yellow Dia. Before Shrink: .488" Dia. After Shrink: .236"
- UL224 Recognized/CSA Listed
- Order Qty of 1 = 1 Kit

DIMENSIONS = INCHES

CAT. NO.	KIT TYPE	CONTENTS				TOTAL PIECES
		LENGTH	COLOR	DIAMETER BEFORE SHRINKING	DIAMETER AFTER SHRINKING	
<b>COLORED KIT</b>						
68320	COLORED KIT	1.375	(5)RED, (5)BLUE, (5)WHITE, (5)YELLOW	.078	.029	20
		1.375	(5)RED, (5)BLUE, (5)WHITE, (5)YELLOW	.098	.039	20
		1.375	(5)RED, (5)BLUE, (5)WHITE, (5)YELLOW	.137	.059	20
		1.375	(5)RED, (5)BLUE, (5)WHITE, (5)YELLOW	.212	.098	20
		2.953	(3)RED, (2)BLUE, (3)WHITE, (2)YELLOW	.251	.117	10
		2.953	(1)RED, (2)BLUE, (1)WHITE, (1)YELLOW	.370	.176	5
		2.953	(1)RED, (2)BLUE, (1)WHITE, (1)YELLOW	.488	.236	5