



MORRIS CAT#: 68321  
Thin Wall Heat Shrink Tubing  
Kits - Black



**Features:**

Thin Wall Heat Shrink Tubing In Kits Black features include:

- Heat Shrink Tubing used for Electrical Insulation, Wire Harness, Bundling, Splices & Terminations
- Pre-Cut Flexible Polyolefin Tubing
- 2:1 Shrink Ratio
- Rated for 600 Volt 257°F (125°C) Continuous Operation
- Heat Shrink Tubing forms tough, smooth insulated covering resistant to common fluids and solvents
- Kit Contents:
  - Length: 1.375" Qty: 20 Black Dia. Before Shrink: .078" Dia. After Shrink: .029"
  - Length: 1.375" Qty: 20 Black Dia. Before Shrink: .098" Dia. After Shrink: .039"
  - Length: 1.375" Qty: 20 Black Dia. Before Shrink: .137" Dia. After Shrink: .059"
  - Length: 1.375" Qty: 20 Black Dia. Before Shrink: .212" Dia. After Shrink: .098"
  - Length: 2.953" Qty: 10 Black Dia. Before Shrink: .251" Dia. After Shrink: .117"
  - Length: 2.953" Qty: 5 Black Dia. Before Shrink: .370" Dia. After Shrink: .176"
  - Length: 2.953" Qty: 5 Black Dia. Before Shrink: .488" Dia. After Shrink: .236"
- UL224 Recognized/CSA Listed
- Order Qty of 1 = 1 Kit

DIMENSIONS = INCHES

CAT. NO.	KIT TYPE	CONTENTS			TOTAL PIECES	
		LENGTH	COLOR	DIAMETER BEFORE SHRINKING		DIAMETER AFTER SHRINKING
<b>BLACK KIT</b>						
68321	BLACK KIT	1.375	(20)BLACK	.078	.029	20
		1.375	(20)BLACK	.098	.039	20
		1.375	(20)BLACK	.137	.059	20
		1.375	(20)BLACK	.212	.098	20
		2.953	(10)BLACK	.251	.117	10
		2.953	(5)BLACK	.370	.176	5
		2.953	(5)BLACK	.488	.236	5