


# 71413A - LED CANOPY LIGHT

120-277V 150W 4000K-5700K








### **FEATURES:**

- Commonly used in gas station, service station, underground parking lot, warehouse, garages etc
- Powder Coated White Color
- Good Heat Dissipation
- CCT Tunable
- Frosted Polycarbonate Lens


- 5 Year Limited Warranty
- IP65 rated
- Certification: cULus
- DLC PRODUCT ID#: PMI3P100
  Environment: Suitable for Wet Locations

Part#	Input/ Wattage	Volts	Lumens	ССТ	CRI	Dimming	Light Pattern	Lumens/ Watt	DLC PRODUCT ID #:
71413A	150	120-277	20,847	4K-57K	>80	N/A	Garage	139	PMI3P100

#### **PHOTOMETRY**



#### The Average Illuminance Effective Figure





# 71413A - LED CANOPY LIGHT

120-277V 150W 4000K-5700K

### **Technical Specifications:**

**Electrical:** 

Input Voltage: 120V-277V Current: 1.1A@120V Frequency: 50/60Hz

Power Factor: ≥.98

THD: ≤20%

**Product Parameters:** 

Input Watts: 150W

Lumens: 20,847

Efficacy: 139 lumens per watt 50,000+ Hour L70 Life Span

CCT: 4000K/4500K/5000K/5700K

**Chromacity Measurements:** 

Beam Angle: 110°

CRI: >80 R9: 9

**Component Specifications:** 

LED: SMD 2835 120-277V, 50-60Hz

Dimming: N/A

**Operating Temperature:** 

Minimum Starting: -40°F to 122°F

**Construction:** 

Housing: Aluminum Alloy

**Powder Coated** 

IP Rating: IP65 suitable for wet locations

Lens Material: Polycarbonate

Mounting: Ceiling

Listings:

cULus

DLC PREMIUM PRODUCT ID#:

PMI3P100

Warranty:

Morris Products carries a 5 year warranty from date of purchase against defects in materials and workmanship (assuming normal

and proper usage).