



MORRIS CAT#: 90554
Copper Mechanical Lugs #8-1/0



Features:

Copper Mechanical Lugs #8-1/0 features include:

- Electrolytic Copper mechanical lugs made from pure 100% conductive electrolytic Copper
- Bright Copper finish standard
- One piece-flat bottomed, for full contact, highest efficiency
- Copper lugs are completely re-usable
- No special installation tools required
- Metal stamped with conductor range
- Suitable for Copper wire only
- 600 Volt
- UL486A/CSA listed
- Dimension Measurements = Inches
- Order Qty of 1 = 1 Piece

UPC Number
Description

One Conductor One Hole
Copper Mechanical Lug

- Features**
- Manufactured from High Strength High Conductivity Copper Alloy
 - Rated For Copper Conductors
 - One Conductor One Hole Configuration

General

Material: Extruded Copper Alloy
Screw Type: Steel Plated Hex Head
Wire Range: #14 - 250 MCM

Dimension Information

See Table

Specifications

Temperature Rating 90° C
Voltage Rating 600
Flammability Rating N/A
Amp Rating To Conductor

Packaging

Box Qty See Table

Certifications

UL UL 486A
CSA Yes
RoHS Yes

DIMENSIONS = INCHES									
CAT. NO.	FIG	WIRE RANGE	BOLT SIZE	DIMENSIONS			PAD THICKNESS	SCREW TYPE	BOX QTY
				LENGTH	WIDTH	HEIGHT			
COPPER - STRAIGHT & ROUND TANG									
90554	4	1/0 - 8	5/16	1-1/2	0.75	0.75	3/32	1/4" HEX	50