




Aluminum Splices/Reducers 2 Screw

MORRIS CAT#'s: 90612-9062



DIMENSIONS = INCHES

<i>CAT. NO.</i>	<i>AWG</i>	<i>FIG</i>	<i>WIRE RANGE</i>	<i>LENGTH</i>	<i>WIDTH</i>	<i>HEIGHT</i>	<i>BOX QTY</i>
90612	2	1	2-14	1.12	.44	.50	50
90614	1/0	1	1/0-14	1.50	.53	.63	25
90615	2/0	1	2/0-8	1.59	.56	.70	25
90616	250	2	4/0-250MCM-6	3.94	1.00	1.13	10
90617	250	1	4/0-250MCM-6	2.00	.84	1.10	10
90620	500	2	500MCM-3/0	4.19	1.36	1.50	3
90624	750	2	750MCM-250MCM	6.06	1.53	1.75	1

Features:

1. Manufactured from High Strength 6061-T6 Aluminum Alloy to Ensure Both Maximum Strength and Conductivity
2. Dual Rated for Both Copper and Aluminum Conductors and Electro-Tin Plated for Low Contact Resistance and Protection Against Corrosion
3. Assembly Can be Made with Only a Screwdriver or Allen Wrench and Connectors Are Re-Usable
4. Rated 600V; 194°F (90°C)
5. 90612-90614 Have Slotted Screws
6. UL486B LISTED AL9CU