

Catalog Number UPC Number Description See Table

Bi-Metallic Pin Terminals Stranded Copper Pin

Features

 Manufactured from High Strength High Conductivity Aluminum Alloy

• Stranded Copper Pin

• Electro Tin Plated

Rated for Aluminum Conductors Only

Oxide Inhibator Coated Barrel

EDPM Rubber Insulating Cover

General

Material: Aluminum Alloy/ Stranded Copper Pin

EDPM Rubber Insulating Cover

Wire Range: Conductor Size Pin Size

¹6 #8

Thru 600 MCM 350 MCM

Dimension Information

Length: See Table

Specifications

Temperature Rating:
Voltage Rating:
600
Flammability Rating:
N/A

Amp Rating: To Conductor

Packaging

Box Qty See Table

Certifications

UL Yes cUL Yes RoHS Yes

Cat No.	Conductor	Stranded Copper Pin	Color Code	Box Qty	
90642	6	8	Gray	50	
90644	4	6	Green	50	
90646	2	4	Pink	25	
90648	1	3	Gold	25	
90650	1/0	2	Tan	25	
90652	2/0	1	Olive	10	
90654	3/0	1/0	Ruby	10	
90658	250 MCM	3/0	Red	10	
90660	300 MCM	4/0	Blue	10	
90663	400 MCM	250MCM	Green	10	
90664	500 MCM	350MCM	Pink	10	
90666	600 MCM	350MCM	Black	10	

