



**Morris CAT#: 90950-90952**  
**Two Conductors Two Hole Mount -**  
**Aluminum Mechanical Lug**



**FIG 11**

**Features:**

- Manufactured from High Strength 6061-T6 Aluminum Alloy to Insure Both Maximum Strength and Conductivity
- Dual Rated for both Copper and Aluminum Conductors
- Electro-Tin Plated for Low Contact Resistance and Protection Against Corrosion
- Assembly can be Made With Only a Screwdriver or Allen Wrench
- Connectors are Re-Usable
- NEMA Standard 1-3/4" Center Hole Spacing
- Rated 600V; 194°F (90°C)
- UL486B LISTED AL9CU

DIMENSIONS = INCHES

<i><b>CAT. NO.</b></i>	<i><b>AWG</b></i>	<i><b>FIG</b></i>	<i><b>WIRE RANGE</b></i>	<i><b>LENGTH</b></i>	<i><b>WIDTH</b></i>	<i><b>HEIGHT</b></i>	<i><b>STUD SIZE</b></i>	<i><b>BOX QTY</b></i>
<b><i>TWO CONDUCTORS - TWO HOLE MOUNT</i></b>								
90950	350	II	350MCM-6SOL.	5.15	1.91	1.22	0.50	4
90951	600	II	600MCM-4SOL.	5.58	2.40	1.57	0.50	2
90952	1000	II	1000MCM-350MCM	5.75	3.56	1.94	0.50	2



Morris CAT#: 90950-90952  
Two Conductors Two Hole Mount -  
Aluminum Mechanical Lug

## Torque Chart

### Tightening Torque Slotted Screws (in-lbs.)

Per UL486A/B Table 23

<i><b>Wire Size</b></i>	<i><b>Torque</b></i>
<b>#2-2/0</b>	50
<b>#4-#6</b>	45
<b>#8</b>	40
<b>#10-#14</b>	35

## Torque Chart

### Tightening Torque Internal Hex Screws (in-lbs.)

Per UL486A/B Table 23

<i><b>Connector Size</b></i>	<i><b>Torque</b></i>
<b>1000</b>	600
<b>750-800</b>	500
<b>500-600</b>	375
<b>250-350</b>	275
<b>1/0-2/0</b>	120