



MORRIS CAT#: 91130-91160

Ground/Neutral Bars



Features:

- Copper & Aluminum Neutral & Ground Bars
- Aluminum Bars are made from 6060-T6 Tin-Plated Aluminum
- Aluminum Bars are Dual Rated for Copper or Aluminum Conductors
- Copper Bars are Rated for Copper Conductors Only
- Available from 2 Circuit to 190 Circuit Configurations
- Range Taking
- 600V

DIMENSIONS = INCHES

CAT. NO.	MATERIAL	WIRE RANGE	NO. OF CIRCUITS	TOTAL NO. HOLES	LENGTH	HEIGHT	WIDTH	HOLE SPACING	MOUNT HOLE POSITION	BOX QTY
ALUMINUM										
91130	ALUMINUM	#14-#4	2	3	.95	.44	.31	.312	2	100
91131	ALUMINUM	#14-#4	4	5	1.57	.44	.31	.312	3	100
91132	ALUMINUM	#14-#4	5	6	1.88	.44	.31	.312	3	100
91133	ALUMINUM	#14-#4	6	7	2.25	.44	.31	.312	4	100
91134	ALUMINUM	#14-#4	4	6	1.88	.44	.31	.312	1 & 4	100
91135	ALUMINUM	#14-#4	5	7	2.25	.44	.31	.312	1 & 7	100
91136	ALUMINUM	#14-#4	5	7	2.25	.44	.31	.312	2 & 6	100
91137	ALUMINUM	#14-#4	6	8	2.56	.44	.31	.312	4 & 7	100
91138	ALUMINUM	#14-#4	7	9	2.87	.44	.31	.312	3 & 7	100
91139	ALUMINUM	#14-#4	9	11	3.50	.44	.31	.312	1 & 11	50
91140	ALUMINUM	#14-#4	10	12	3.81	.44	.31	.312	1 & 12	50
91141	ALUMINUM	#14-#4	12	14	4.43	.44	.31	.312	1 & 14	50
91142	ALUMINUM	#14-#4	15	17	5.37	.44	.31	.312	1 & 17	50
91143	ALUMINUM	#14-#4	20	22	6.93	.44	.31	.312	1 & 22	50
91144	ALUMINUM	#14-#4	190	190	60.0	.44	.31	.312	-	10
91145	ALUMINUM	#14-#2	10	12	4.12	.50	.38	.34	3 & 11	50
91146	ALUMINUM	#14-2/0	2	3	1.75	.75	.56	.60	2	25
91147	ALUMINUM	#14-2/0	3	5	2.95	.75	.56	.60	2 & 4	25
91148	ALUMINUM	#14-2/0	6	8	4.75	.75	.56	.60	1 & 8	25
COPPER										
91152	COPPER	#14-#4	4	6	1.94	.44	.31	.312	1 & 6	100
91153	COPPER	#14-#4	5	7	2.25	.44	.31	.312	1 & 7	100
91154	COPPER	#14-#4	6	8	2.56	.44	.31	.312	1 & 8	100
91155	COPPER	#14-#4	12	14	4.43	.44	.31	.312	1 & 14	50
91156	COPPER	#14-#4	13	15	4.74	.44	.31	.312	3 & 13	50
91157	COPPER	#14-#4	13	15	4.74	.44	.31	.312	6 & 11	50
91158	COPPER	#14-#4	190	190	60.0	.44	.31	.312	-	10
91159	COPPER	#14-#2	3	5	2.00	.50	.38	.397	1 & 5	50
91160	COPPER	#14-#2	6	8	3.25	.50	.38	.397	2 & 7	50