



Catalog Number	See Table
UPC Number	See Table
Description	Copper Long Barrel 1 Hole Compression Connector




Features

- Manufactured from High Strength High Conductivity Seamless Copper Tubing
- Electro-Tin Plated
- Color coded & Marked with die size and crimp marks
- Peep Hole

General

Wire Size	#8 Str thru 750 MCM
Material	High Conductivity Seamless Copper Tubing
Material Treatment	Electro-Tin Plating
Stud Configuration	1 Hole
Stud Size	See Table



Dimension Information

See Table

Specifications

Temperature Rating	90° C
Voltage Rating	35 KV
Flammability Rating	N/A
Amp Rating	To Conductor

Packaging

Box Qty	See Table
---------	-----------

Certifications

UL	UL486A
cUL	Yes
RoHS	Yes

Copper Short Barrel 1 Hole Compression Connector

Cat. No.	Wire Size	Stud Size	Color Code	ID	OD	A	A1	B	C	D	E	F
94210	8 Str.	#10	Red	.0173	0.271	1.51(38.6)	.80(20.5)	.42(10.6)	0.08	0.21	0.28	0.59
94211	8 Str.	1/4	Red	0.173	0.271	1.52(38.6)	.81(20.5)	.42(10.6)	0.08	0.25	0.28	0.59
94213	6 Str.	#10	Blue	.204(5.2)	0.295	1.77(45.0)	.98(25.0)	.42(10.7)	0.08	0.21	0.3	0.64
94214	6 Str.	1/4	Blue	.204(5.2)	0.295	1.77	0.98	.42(10.7)	0.08	0.25	0.3	0.67
94215	6 Str.	5/16	Blue	.204(5.2)	0.295	1.91(48.5)	.98(24.9)	.59(15.0)	0.08	0.33	0.37	0.81
94216	6 Str.	3/8	Blue	.204(5.2)	0.295	1.91(48.5)	.98(24.9)	.59(15.0)	0.08	0.41	0.37	0.81
94217	4 Str.	#10	Gray	.251(6.4)	0.342	1.77(45.0)	.98(24.9)	.49(12.4)	0.09	0.25	0.31	0.67
94218	4 Str.	1/4	Gray	.251(6.4)	0.342	1.77	0.98	.49(12.4)	0.09	0.25	0.29	0.65
94219	4 Str.	5/16	Gray	.251(6.4)	0.342	1.77(45.0)	.98(24.9)	.49(12.4)	0.09	0.33	0.31	0.67
94220	4 Str.	3/8	Gray	.251(6.4)	0.342	1.91(48.5)	.98(24.9)	.59(15.0)	0.09	0.41	0.37	0.81
94221	2 Str.	1/4	Brown	.314(8.0)	.421(10.7)	2.07(52.6)	1.10(27.9)	.60(15.2)	0.1	0.25	0.37	0.81
94222	2 Str.	5/16	Brown	.314(8.0)	.421(10.7)	2.07(57.0)	1.10(31.8)	.60(15.3)	0.1	0.33	0.37	0.81
94223	2 Str.	3/8	Brown	.314(8.0)	.421(10.7)	2.07(52.6)	1.10(27.9)	.60(15.2)	0.1	0.41	0.37	0.81
94226	1 Str.	5/16	Green	.358(9.1)	.468(11.9)	2.11(59.0)	1.10(31.8)	.67(17.1)	0.11	0.33	0.37	0.81
94227	1 Str.	3/8	Green	.358(9.1)	.468(11.9)	2.21(56.1)	1.10(27.9)	.67(17.1)	0.11	0.41	0.37	0.81
94230	1/0 Str.	5/16	Pink	.389(9.9)	.519(13.2)	2.21(56.0)	1.20(35.1)	.74(18.9)	0.13	0.33	0.37	1.06(26.9)
94234	1/0 Str.	3/8	Pink	.389(9.9)	.519(13.2)	2.20(55.0)	1.20(35.1)	.74(18.9)	0.13	0.41	0.41	1.06(26.9)
94235	1/0 Str.	1/2	Pink	.389(9.9)	.519(13.2)	2.50(63.5)	1.20(30.4)	.74(18.9)	0.13	0.51	0.47	1.06(26.9)
94238	2/0 Str.	3/8	Black	.440(11.2)	.562(14.3)	2.68(67.0)	1.38(38.1)	.81(20.7)	0.12	0.41	.41(10.2)10.2	1.06
94239	2/0 Str.	1/2	Black	.440(11.2)	.562(14.3)	2.68(68.0)	1.38(35.0)	.81(20.5)	0.12	0.51	.41(10.2)10.2	1.06(26.9)
94245	3/0 Str.	3/8	Orange	.492(12.5)	.622(15.8)	2.80(71.1)	1.38(35.0)	.90(22.9)	0.13	0.41	0.47	1.06(26.9)
94246	3/0 Str.	1/2	Orange	.492(12.5)	.622(15.8)	2.8	1.38	.90(22.9)	0.13	0.51	0.47	1.06(26.9)
94253	4/0 Str.	3/8	Purple	.547(13.9)	.688(17.5)	2.80(71.1)	1.38(35.0)	.90(22.9)	0.13	0.41	0.47	1.06(26.9)
94254	4/0 Str.	1/2	Purple	.547(13.9)	.688(17.5)	3.23(82.0)	1.62(41.1)	1.00(25.4)	0.13	0.51	0.52	1.06(26.9)
94257	250 MCM	3/8	Yellow	.594(15.1)	0.751	3.03	1.61	1.09	0.15	0.41	0.52	1.06
94258	250 MCM	1/2	Yellow	.594(15.1)	0.751	3.03(82.0)	1.61(41.1)	1.09(27.7)	0.15	0.51	0.52	1.06(26.9)
94262	300 MCM	1/2	White	.657(16.7)	.814(20.7)	3.39(91.0)	1.97(50.1)	1.19(30.2)	0.15	0.51	0.52	1.06(26.9)
94266	350 MCM	1/2	Red	.700(17.8)	.874(22.2)	3.46(94.0)	1.97	1.28(32.4)	0.17	0.51	0.52	1.06(26.9)
94267	350 MCM	5/8	Red	.700(17.8)	.874(22.2)	3.46(87.8)	1.97(50.0)	1.28(32.4)	0.17	0.67	0.51	1.06(26.9)
94270	400 MCM	1/2	Blue	.763(19.4)	.948(24.1)	3.86	1.97	1.39(35.2)	0.18	0.51	0.51	1.38(34.3)
94274	400 MCM	5/8	Blue	.763(19.4)	.948(24.1)	3.86	1.97	1.39(35.2)	0.18	0.51	0.51	1.38(34.3)
94278	500 MCM	1/2	Brown	.834(21.2)	1.06(27.0)	4.13(112.0)	2.24(57.2)	1.54(39.1)	0.22	0.51	0.51	1.38
94282	500 MCM	5/8	Brown	.834(21.2)	1.06(27.0)	4.13(112.0)	2.24(57.2)	1.54(39.1)	0.22	0.51	0.51	1.38
94286	600 MCM	5/8	Green	.925(23.5)	1.18(30.2)	4.25(122.0)	2.24(63.5)	1.72(43.6)	0.25	0.67	0.69	1.46(36.8)
94290	750 MCM	5/8	Black	1.03(26.2)	1.31(33.3)	5.16(134.0)	2.64(73.2)	1.90(48.3)	0.27	0.67	0.69	1.85(36.8)
94292	1000 MCM	5/8	White	1.15	1.5	5.625	2.87	2.15	0.33	0.67	0.86	1.74