



Flex Duplex Box Connectors - Zinc Die Cast



FIG 1




FIG 1



FIG 2




FIG 2


- Use to connect two pieces of Flexible Metallic Conduit, AC, MC, or NM sheathed cable to a steel box or other metal enclosure when using only one knockout opening:
 - 14/2 Thru 12/3 NM
 - 14/2 Thru 10/4 AC
 - 14/2 Thru 10/3 MC
 - 3/8" FMC
- 3/8" size fits 1/2" knockout
- One Screw or Two Screw design

DIMENSIONS = INCHES

CAT. NO.	TRADE SIZE	FIGURE	# OF SCREWS	DIMENSIONS			INNER BOX	OUTER BOX
				A	B	C		
15065	3/8"	1	1	1.59	1.62	0.46	25	250
15066	3/8"	2	2	1.57	.61	2.32	25	250

BX - Flex - MC

90° Flex Conduit Duplex Box Connector - Zinc Die Cast




- Use to connect two pieces of Flexible Metallic Conduit, AC, MC or NM sheathed cable to a steel outlet box or other metal enclosure when using only one knockout opening in a dry location:
 - 14/2 Thru 10/3 NM
 - 14/2 Thru 10/4 AC
 - 14/2 Thru 10/3 MC
 - 3/8" FMC
- 3/8" size fits 1/2" knockout
- Two Combo Head Mounting Screws

DIMENSIONS = INCHES

CAT. NO.	TRADE SIZE	DIMENSIONS			INNER BOX	OUTER BOX
		A	B	C		
15067	3/8"	2.02	1.64	1.24	25	250

Anti-Short Bushings



- Insulates conductor from cut armor ends on flexible BX or Greenfield conduit
- Inserted into I.D. at termination point
- Overlapping horizontal flange protects against sharp metal edges
- Tapered design assures fast insertion
- Extra length assures positive grip
- Polypropylene material resists weather extremes, oil, moisture and chemicals
- Rated up to 194°F

DIMENSIONS = INCHES

CAT. NO.	SIZE	CABLE SIZES	DIMENSIONS				BAG QTY
			A	B	C	D	
21752	0	14/2, 14/3, 12/2	.56"	.671"	.38"	.312"	35
21753	1	14/4, 12/3, 6/1, 4/1	.65"	.671"	.45"	.312"	35
21754	2	12/4, 10/2, 10/3, 2/1	.61"	.859"	.58"	.125"	35
21755	3	10/4, 8/2, 8/3, 1/1	.67"	1.046"	.79"	.109"	20
21756	4	8/4, 6/4, 6/3, 6/2, 4/3, 4/2	.83"	1.266"	1.00"	.156"	16