

## MORRIS CAT#: G14050 1/4" - 2" Master Boot Universal Roof Flashings



## Features:

1/4" - 2" Master Boot Universal Roof Flashings features include:

- Universal flashing can be used with any type of corrugated roofing material, ie: asphalt, plastic, tile, rubber, metal, etc. (not for hot mopped or built-up roofs)
- Self-sealing Step-Cone boot made of premium grade E.P.D.M., which gives it maximum resistance to weathering due to ozone & UV light
- Flexible Aluminum Alloy rim assures universal flashing form fits and has corrosion resistance excellent for ribbed metal roofs
- Provides a Permanent Seal that is unaffected by expansion/contraction, vibration, ice, snow, hailstones, etc
- Installs in about 10 minutes
- Excellent for wall penetrations weathertight and airtight, inside or outside
- Easily customized with sharp knife/scissors to accommodate a broad range of diameters
- Slides over vent pipe & conforms to any roof pitch
- Order Qty of 1 = 1 Piece

CAT. NO.	OLD CAT. No.	OUTSIDE DIAMETER OF PIPE TO BE FLASHED	BASE		CASE	WT/
			LENGTH	WIDTH	ŌΤΥ	CAŜE
G16250		1/8" TO 3/4"	2-1/4"	2-1/4"	12	2
G14050	G16251	1/4" TO 2-3/4"	4-1/2"	4-1/2"	6	2
G14051	G16252	7/8" TO 4"	6"	6"	6	3
G14052	G16253	I/4" TO 5-3/4"	8"	8"	6	4