



**MORRIS CAT#: G14052**  
**1/4" - 5-3/4"**  
**Master Boot Universal Roof Flashings**



**Features:**

- Universal flashing can be used with any type of corrugated roofing material, ie: asphalt, plastic, tile, rubber, metal, etc. (not for hot mopped or built-up roofs)
- Self-sealing Step-Cone boot made of premium grade E.P.D.M., which gives it maximum resistance to weathering due to ozone & UV light
- Flexible Aluminum Alloy rim assures universal flashing form fits and has corrosion resistance - excellent for ribbed metal roofs
- Provides a Permanent Seal that is unaffected by expansion/contraction, vibration, ice, snow, hailstones, etc.
- Installs in about 10 minutes
- Excellent for wall penetrations - weathertight and airtight, inside or outside
- Easily customized with sharp knife/scissors to accommodate a broad range of diameters
- Slides over vent pipe & conforms to any roof pitch

| <i><b>CAT. NO.</b></i> | <i><b>OLD CAT. NO.</b></i> | <i><b>OUTSIDE DIAMETER OF PIPE TO BE FLASHED</b></i> | <i><b>BASE</b></i>   |                     | <i><b>CASE QTY</b></i> | <i><b>WT/ CASE</b></i> |
|------------------------|----------------------------|--|----------------------|---------------------|------------------------|------------------------|
|                        |                            |  | <i><b>LENGTH</b></i> | <i><b>WIDTH</b></i> |                        |                        |
| G14052                 | G16253                     | 1/4" TO 5-3/4"                                       | 8"                   | 8"                  | 6                      | 4                      |