

Type S Non-Tamper Fuses



- Rejection Base, Dual-Element, Time-Delay
- Size rejection feature helps to prevent overfusing
- Heavy duty dual-element construction
- Superior overload and short-circuit protection
- Visual indication of good or blown condition
- Interrupting Rating: 10kA RMS Amps
- 125 VAC
- UL Listed, C.S.A. Certified

CAT. NO.	DESCRIPTION	BOX QTY	MIN. ORDER QTY
T626-6S	TYPE "S" FUSE - 6.25 AMP	4	4
T626-15S	TYPE "S" FUSE - 15 AMP	4	4
T626-20S	TYPE "S" FUSE - 20 AMP	4	4

Type TL Plug Fuses



- Time-delay construction withstands light motor loads
- Edison base threads into non-rejection fuse receptacles
- For upgrade refer to "T" fuse
- Glass top for safety against shock
- Positive visual indication of OK condition or blown condition
- Distinguishes between overload and dead short conditions
- Magnifying center of face
- Interrupting Rating: 10kA RMS Amps
- Meets Federal Specification WF 791E/Gen. Type 791/1. Base "W" fuses
- 125 VAC
- UL Listed

CAT. NO.	DESCRIPTION	BOX QTY	MIN. ORDER QTY
T626-15	PLUG FUSE TYPE TL - 15 AMP	4	4
T626-20	PLUG FUSE TYPE TL - 20 AMP	4	4
T626-25	PLUG FUSE TYPE TL - 25 AMP	4	4
T626-30	PLUG FUSE TYPE TL - 30 AMP	4	4

Fuse Pullers



T626-38071



T626-38073

- Fuse pullers are used to safely pull fuses

CAT. NO.	DESCRIPTION	CASE QTY
T626-38071	FUSE PULLER - FOR FUSE SIZES 1/4" TO 1/2"	1
T626-38073	FUSE PULLER - FOR FUSE SIZES 1" TO 1-3/4"	1

Box Cover Units



T620-608

- Maximum Amps: 15
- Maximum AC voltage of 125
- Designed for use with the Type T plug fuses
- UL Listed and C.S.A. Certified

CAT. NO.	DESCRIPTION	UOM	ORDER MULTIPLE
T620-608	SWITCH/FUSE COMBO (ESSU)	EA	60
T620-6081	PLUG FUSE BASE ONLY (ESOU)	EA	50
T620-6082	RECEPTACLE/FUSE COMBO (ESRU)	EA	1
T620-6083	SWITCH/FUSE COMBO SQUARE (ESSY)	EA	50

Type T Time Delay Plug Fuses



- Heavy duty dual-element construction for motor circuits
- Edison base threads into non-rejection fuse receptacles
- Superior overload and short-circuit protection
- Interrupting Rating: 10kA RMS Amps
- 125 VAC
- U.L. Listed
- UL Type T

CAT. NO.	DESCRIPTION	BOX QTY	MIN. ORDER QTY
T626-10T	TYPE "T" PLUG FUSE - 10 AMP	4	4
T626-15T	TYPE "T" PLUG FUSE - 15 AMP	4	4
T626-20T	TYPE "T" PLUG FUSE - 20 AMP	4	4
T626-25T	TYPE "T" PLUG FUSE - 25 AMP	4	4
T626-30T	TYPE "T" PLUG FUSE - 30 AMP	4	4

Blade (Auto) Fuses



- These fuses are fast acting low voltage supplementary fuses
- Automotive blade style fuse
- UL Recognized

CAT. NO.	DESCRIPTION	BOX QTY	MIN. ORDER QTY
T626-AT0003	BLADE FUSE - 3 AMP - PURPLE, PACK OF 5	100	100
T626-AT0005	BLADE FUSE - 5 AMP - TAN, PACK OF 5	100	100

Fuse Adapters



T626-ESA15



T626-38632

- Fuse adapters are used to retrofit fuses into existing installations
- Class H/S
- UL & CSA Listed

CAT. NO.	DESCRIPTION	BOX QTY	MIN. ORDER QTY
T626-38632	FUSE ADAPTER - 60 TO 30 REDUCER FOR CLASS H, 250V	10	1
T626-38636	FUSE ADAPTER - 60 TO 30 REDUCER FOR CLASS H, 600V	10	1
T626-ESA15	FUSE ADAPTER - 15 AMP TYPE S FUSES	4	4
T626-ESA20	FUSE ADAPTER - 20 AMP TYPE S FUSES	4	4