



Fuseblocks - Class RK

- Class RK Fuseblocks
- The fuse blocks are designed to allow the fuse to blow or burn out before the component can be damaged
- UL & CSA Listed



CAT.NO.	DESCRIPTION	CASE QTY
250V		
TRM25060-ICR	FUSEBLOCK - 1 POLE CLASS RK 250V 60A	1
TRM250100-ICR	FUSEBLOCK - 1 POLE CLASS RK 250V 100A	1
TRM250200-ICR	FUSEBLOCK - 1 POLE CLASS RK 250V 200A	1
600V		
TRM60060-ICR	FUSEBLOCK - 1 POLE CLASS RK 600V 60A	1
TRM600100-ICR	FUSEBLOCK - 1 POLE CLASS RK 600V 100A	1
TRM600200-ICR	FUSEBLOCK - 1 POLE CLASS RK 600V 200A	1

Heavy Duty Solenoid Voltage & Continuity Tester

- Test Voltage from 120V to 600V AC/DC
- Non-Contact Voltage Sensor from 90V to 1000V
- Test Continuity & Polarity
- Case serves as prod holder for one-hand operation
- Self-Storing prods
- Solenoid Sensing indicated by LEDs & Vibration
- Ergonomic Soft PVC housing for comfort grip
- LED Spotlight Illuminates Work Area
- Battery not Included (AAA x 1)



CAT. NO.	CASE QTY
59100	60



Auto-Ranging Digital Multimeter with Temperature Probe

- AC Voltage: 4V/40V/400V/600V \pm (1.2%+5)
- DC Voltage: 400mV/4V/40V/400V/600V \pm (0.5%+3)
- DC Current: 400uA/4000uA/40mA/400mA \pm (1.0%+5)
10A \pm (2.0%+10)
- AC Current: 400uA/4000uA/40mA/400mA \pm (1.2%+5)
10A \pm (2.5%+10)
- Resistance: 400 Ω /4K Ω /40K Ω \pm (0.8%+5)
400K Ω /4M Ω /40M Ω \pm (0.8%+5)

CAT. NO.	DESCRIPTION	CASE QTY
MS8239C	DIGITAL MULTIMETER	1



Fuseblocks - Class H

- Class H Fuseblock
- The fuse blocks are designed to allow the fuse to blow or burn out before the component can be damaged
- UL & CSA Listed



CAT. NO.	DESCRIPTION	CASE QTY
T626-2631I	FUSEBLOCK - 3 POLE BOX LUG CLASS H, 250V	1

Professional Infrared Thermometer with Laser Pointer



- Safely measure hot, hazardous, or hard-to-reach materials without touching the material's surface; simply pull the trigger & read the temperature
- $^{\circ}$ C/ $^{\circ}$ F switchable & reading hold
- Measuring Ranges: -4 $^{\circ}$ F to 932 $^{\circ}$ F (-20 $^{\circ}$ C to 500 $^{\circ}$ C)
- Min/AVG Reading
- Low Battery Display
- Dimensions: 5.6" x 3.9" x 1.85"
- Weight: 4.8 oz.
- Power: 2 AAA Batteries (Included)



CAT. NO.	DESCRIPTION	CASE QTY
MS6522B	INFRARED THERMOMETER	1



- Frequency: 100Hz/1000Hz/10kHz \pm (1.5%+5)
- Temperature: -4 $^{\circ}$ F to 1832 $^{\circ}$ F (-20 $^{\circ}$ C to 1000 $^{\circ}$ F)
- Auto or Manual Ranging
- Display: 4000 Counts
- Diode Open Voltage 1.5V
- Data Hold
- Continuity Buzzer: <50 \pm 20 Ω
- Auto Power Off
- Backlit Display
- Low Battery Display
- Power Source: (2) 1.5V AAA Batteries
- CAT III 600V
- Dimensions: 5.9" X 2.9" X 1.6"
- Weight: 7.04 OZ

Non-Contact Power Detector 100-240 Volts AC

- Locates breaks along live, insulated wires and power cord
- Detects voltage at outlet, lighting fixture, circuit breaker, cable
- Convenient pen size fits into pocket or tool pouch
- Audible and visual indication
- 3/16" Detection Distance



CAT. NO.	CASE QTY
59112	120