

# Submersible Insulated Splice Connectors



- Designed for use in Direct Burial & Submersible installations such as hand holes, below grade boxes, in the ground or submersed in water
- Range Taking Design Reduces Inventory
- AL9CU Dual Rated for Copper & Aluminum Conductors
- Insulated with High Dielectric Strength Rubber Compound
- Molded for Precise Fit & supplied with removable access plugs over the hex screws

- Eliminates the need for Taping, Heat Shrink etc.
- Abrasion and Chemical Resistant, will not support combustion
- Meets or exceeds ANSI C119.1 Specifications for a Submersible Connection
- UL Listed for Wet or Damp Locations, Direct Burial & Submersible per UL486D
- Rated 600 Volts, Cold Temperature UL tested to 0°F



DIMENSIONS = INCHES

| CAT. NO. | WIRE RANGE AWG | WIRE RANGE (INCHES) | BOLT SIZE | DIMENSIONS (INCHES) |      |      | CASE QTY |
|----------|----------------|---------------------|-----------|---------------------|------|------|----------|
|          |                |                     |           | H                   | W    | L    |          |
| 98012    | 2/0-14         | .365-.064           | 3/16      | 2.13                | 0.88 | 5.50 | 25       |
| 98014    | 350-12         | .58-.08             | 5/16      | 3.16                | 1.44 | 8.14 | 50       |

# Submersible Insulated Pedestal Connectors

- Designed for use in Direct Burial & Submersible installations such as hand holes, below grade boxes, in the ground or submersed in water
- Range Taking Design Reduces Inventory
- Dual Rated for Copper & Aluminum Conductors
- Insulated with High Dielectric Strength Rubber Compound
- Molded for Precise Fit & supplied with removable access plugs over the hex screws

- Eliminates the need for Taping, Heat Shrink etc.
- Abrasion and chemical resistant, Will not support combustion
- Meets or exceeds ANSI C119.1 Specifications for a Submersible Connection
- Rated 600 Volts, Cold Temperature UL tested to 0°F



DIMENSIONS = INCHES

| CAT. NO. | NUMBER OF PORTS | WIRE RANGE AWG | WIRE RANGE | BOLT SIZE | DIMENSIONS (INCHES) |      |       | CASE QTY |
|----------|-----------------|----------------|------------|-----------|---------------------|------|-------|----------|
|          |                 |                |            |           | H                   | W    | L     |          |
| 98023    | 3               | 350-12         | .58"-.08"  | 5/16      | 2.46                | 4.06 | 3.63  | 25       |
| 98024    | 4               | 350-12         | .58"-.08"  | 5/16      | 2.46                | 4.06 | 4.75  | 20       |
| 98026    | 6               | 350-12         | .58"-.08"  | 5/16      | 2.46                | 4.06 | 7.00  | 20       |
| 98033    | 3               | 600-12         | .89"-.08"  | 5/16      | 3.13                | 5.46 | 4.87  | 12       |
| 98034    | 4               | 600-12         | .89"-.08"  | 5/16      | 3.13                | 5.46 | 6.56  | 12       |
| 98036    | 6               | 600-12         | .89"-.08"  | 5/16      | 3.13                | 5.46 | 9.94  | 6        |
| 98038    | 8               | 600-12         | .89"-.08"  | 5/16      | 3.13                | 5.46 | 13.31 | 4        |

# Submersible Insulated Streetlighting Connectors



- Designed for use in Direct Burial & Submersible Streetlighting applications such as hand holes, below grade boxes, in ground or water
- Range Taking Design Reduces Inventory
- AL9CU Dual Rated for Copper & Aluminum Conductors
- Insulated with High Dielectric Strength Rubber Compound
- Molded for Precise Fit & supplied with removable access plugs over the hex screws

- Eliminates the need for Taping, Heat Shrink etc.
- Abrasion and chemical resistant, will not support combustion
- Meets or exceeds ANSI C119.1 Specifications for a Submersible Connection
- UL Listed for Wet Locations, Direct Burial & Submersible per UL486D
- Rated 600 Volts, Cold Temperature UL tested to 0°F

CAN BE USED FOR ANY TYPE OF SPICE

DIMENSIONS = INCHES

| CAT. NO. | FIG | NUMBER OF PORTS | WIRE RANGE AWG | WIRE RANGE (INCHES) | BOLT SIZE | DIMENSIONS (INCHES) |      |      | CASE QTY |
|----------|-----|-----------------|----------------|---------------------|-----------|---------------------|------|------|----------|
|          |     |                 |                |                     |           | H                   | W    | L    |          |
| 98042    | 1   | 2               | 2/0-14         | .365-.064           | 3/16      | 2.13                | 2.75 | 1.80 | 40       |
| 98043    | 1   | 3               | 2/0-14         | .365-.064           | 3/16      | 2.13                | 2.75 | 2.65 | 25       |
| 98044    | 1   | 4               | 2/0-14         | .365-.064           | 3/16      | 2.13                | 2.75 | 3.49 | 25       |
| 98046    | 1   | 6               | 2/0-14         | .365-.064           | 3/16      | 2.13                | 2.75 | 5.17 | 25       |
| 98052    | 2   | 3               | 2/0-14         | .365-.064           | 3/16      | 2.13                | 4.25 | 2.65 | 25       |



FIG 1



FIG 2