

Single Speed Condenser Fan Motors



- Installs with all Standard 48 Frame Mounting Brackets
- Standard Shaft Length, Diameter, and Flats
- Drain Holes with Plugs in both end plates
- Automatic Thermal Overload Protector
- Standard 48 Frame Motor Casing Size
- Low Power Consumption
- 60° C Ambient Design
- Electrically Reversible
- Continuous Air Over
- Class B Insulation
- Quiet Operation
- Extended Studs
- 30" Leads
- 60 HZ
- cURus Listed
- Shaft Diameter 1/2"



BALL BEARINGS NOW STANDARD

CAT. NO.	HP	VOLTAGE	SPEED	FLA	UOM	ORDER MULTIPLE
TWG840727	1/6	208-230	1075/1	1.3	EA	1
TWG840728	1/4	208-230	1075/1	2.2	EA	1
TWG840729	1/3	208-230	1075/1	2.8	EA	1
TWG840730	1/2	208-230	1075/1	4.2	EA	1
TWG840731	3/4	208-230	1075/1	4.5	EA	1
TWG840204	1/4	208-230	825/1	1.5	EA	1
TWG840205	1/3	208-230	825/1	2.2	EA	1


Direct Drive Furnace Blower Motors



- Installs with all Standard 48 Frame Mounting Brackets
- Standard Shaft Length, Diameter, and Flats
- Uses 370V Capacitors
- Standard 48 Frame Motor Casing Size
- 2.5" Diameter Hub Rings included
- Low Power Consumption
- Automatic Thermal Overload Protector
- Continuous Duty, Air Over
- Electrically Reversible
- Class B Insulation
- Speed: 1075/3
- Quiet Operation
- 60 HZ
- cURus Listed
- Shaft Diameter 1/2"

CAT. NO.	HP	VOLTAGE	SPEED	FLA	UOM	ORDER MULTIPLE
TWG840583	1/4	115	1075/3	4.6	EA	1
TWG840584	1/4	208-230	1075/3	2.2	EA	1
TWG840585	1/3	115	1075/3	6.7	EA	1
TWG840586	1/3	208-230	1075/3	2.9	EA	1
TWG840587	1/2	115	1075/3	10.2	EA	1
TWG840588	1/2	208-230	1075/3	5.0	EA	1
TWG840589	3/4	115	1075/3	11.3	EA	1
TWG840590	3/4	208-230	1075/3	5.4	EA	1
TWG840595	1	115	1075/3	12.6	EA	1
TWG840596	1	208-230	1075/3	5.59	EA	1

Multiple Horsepower Condenser Fan Motors



- The Multi-Horsepower motors are specially designed to cover a range of applications.
- The condenser fan motors horsepower ranges from 1/2 to 1/5; 1/3 to 1/6 both at 1075 rpm; 1/3 to 1/6 at 825 RPM
- Reversing plugs.
- Extended thru bolts.
- 36 inch leads.
- Designed for 370 Volt capacitors.
- Installs with all 48 frame mounting brackets.
- cURus Listed
- Shaft Diameter 1/2"

CAT. NO.	APPLICATION	VOLTAGE	SPEED	(1) HP-FLA	(2) HP-FLA	(3) HP-FLA	(4) HP-FLA	(5) HP-FLA	UOM	ORDER MULTIPLE
TWG840465	CF	208-230	1075/2	1/3-2.8	1/4-2.0	1/5-1.7	1/6-1.5	-	EA	1
TWG840468	CF	208-230	1075/2	1/2-3.0	1/3-2.5	1/4-2.0	1/5-1.3	-	EA	1
TWG840469	CF	208-230	825/2	1/3-2.1	1/4-1.7	1/5-1.5	1/6-1.2	-	EA	1

Multiple Horsepower Condenser Fan Motors



- The blower motors range from 1/2 to 1/6; 3/4 to 1/5 both at 1075rpm.
- Motors horsepower range from 3/4 to 1/5 in both 115 and 230 Volts all at 1075 RPM
- Reversing plugs.
- Extended thru bolts.
- 36 inch leads.
- Designed for 370 Volt capacitors.
- Installs with all 48 frame mounting brackets.
- cURus Listed
- Shaft Diameter 1/2"

CAT. NO.	APPLICATION	VOLTAGE	SPEED	(1) HP-FLA	(2) HP-FLA	(3) HP-FLA	(4) HP-FLA	(5) HP-FLA	UOM	ORDER MULTIPLE
TWG840463	DDFB	115	1075/4	1/2-7.0	1/3-6.7	1/4-4.4	1/5-3.2	1/6-2.4	EA	1
TWG840464	DDFB	208-230	1075/4	1/2-3.9	1/3-3.6	1/4-2.5	1/5-1.8	1/6-1.3	EA	1
TWG840466	DDFB	115	1075/4	3/4-8.1	1/2-6.6	1/3-4.6	1/4-3.8	1/5-3.1	EA	1
TWG840467	DDFB	208-230	1075/4	3/4-3.8	1/2-3.7	1/3-2.5	1/4-1.8	1/5-1.7	EA	1