



Wall Mount Occupancy/Vacancy Sensor - Double Pole - PIR

- The Passive Infrared (PIR) sensor detects motion by sensing the difference between body heat and ambient room temperature
- Wall switch works best in offices, conference rooms and commonly used areas
- Vacancy Setting allows for Manual ON/Auto OFF Function
- LED indicator for visibility in darkened rooms
- 30Ft Range When Mounted at 4Ft Height
- Adjustable Light Level Sensitivity Settings
- Time delay Off setting is adjustable from 5 Seconds to 30 minutes
- Removable Cover with mode settings and dip switch adjustments
- Decorative Wall Plate Included
- Compatible with Incandescent, Electronic Ballast Fluorescent, Compact Fluorescent, Magnetic Low Voltage, Electronic Low Voltage, LED lighting
- Button 1: Manual On/Auto Off; Button 2: Standby & DCC/VAC Selectable
- Conforms to California Title 24 Energy Code
- Neutral Required for Cat#: 80544



CAT. NO.	COLOR	SWITCH TYPE	SWITCH CONFIGURATION	INCANDESCENT/FLUORESCENT RATING	COVERAGE	VOLTAGE	LED WATTS	CASE QTY
80544	WHITE	ON/OFF AUTO MANUAL ON/AUTO OFF	DOUBLE POLE	800W @ 120V	180°	120V	150W	50
80548	WHITE	ON/OFF AUTO MANUAL ON/AUTO OFF	DOUBLE POLE	800W @ 120V 1200W @ 277V	180°	120-277V	150W	50



Ceiling Sensor Switch - PIR

- The Passive Infrared (PIR) sensor detects motion by sensing the difference between body heat and ambient room temperature
- Adjustable Light Level Sensitivity Settings
- Auto ON/OFF
- Time delay Off setting is adjustable from 15 seconds to 30 minutes
- No ground required
- Compatible with Incandescent, Electronic Ballast Fluorescent, Compact Fluorescent, Magnetic Low Voltage, Electronic Low Voltage, LED lighting
- Polycarbonate
- Conforms to California Title 24 Energy Code
- No Separate Power Pack Required



CAT. NO.	COLOR	INCANDESCENT/FLUORESCENT RATING	COVERAGE	VOLTAGE	CASE QTY
80552	WHITE	800W @ 120V 1200W @ 277V	360° 20 FT DIAMETER @ 15 FT HEIGHT 15 FT DIAMETER @ 10 FT HEIGHT	120-277V	50



Hi-Bay Sensor Switch - PIR

- The Passive Infrared (PIR) sensor detects motion by sensing the difference between body heat and ambient room temperature
- Threaded Stem For Mounting In Linear High-Bay Fixture
- Adjustable Light Level Sensitivity Settings
- Time delay Off setting is adjustable from 15 seconds to 30 minutes
- No ground required
- Compatible with Incandescent, Electronic Ballast Fluorescent, Compact Fluorescent, Magnetic Low Voltage, Electronic Low Voltage, LED lighting
- Polycarbonate
- Conforms to California Title 24 Energy Code
- No Separate Power Pack required



CAT. NO.	COLOR	INCANDESCENT/FLUORESCENT RATING	COVERAGE	VOLTAGE	CASE QTY
80556	WHITE	800W @ 120V 1200W @ 277V	360° - 30FT HEIGHT & 40FT DIAMETER	120-277V	50

