

# Tamper Resistant Duplex Receptacles

- 2 Pole 3 Wire
- Back & Side Wired
- Made of GE Lexan, Steel Mounting Strap
- Washer Type Break Off Plaster Ears
- Large Head Captive Tri-Combination Screws
- Built-in Protective Shutter Mechanism Designed to Prevent Insertion of Foreign Objects
- Clear Visible "TR" marking on Face
- Green Hex-Head Ground Screw
- UL 94V-2 Flame Rating
- Temperature Rating: -40°F to 167°F
- Accepts #12 or #14 Stranded or Solid CU (Push-In #14 Solid Only)



AMPS	VOLTAGE	COLOR	RESIDENTIAL GRADE	COMMERCIAL GRADE	COMMERCIAL GRADE SINGLE RECEPTACLE	BOX QTY	CASE QTY
<b>15 AMP 125V 5-15R</b>							
15	125	IVORY	81950	82435	82510	10	200
		WHITE	81951	82436	82511	10	200
		ALMOND	81953			10	200
<b>20 AMP 125V 5-20R</b>							
20	125	IVORY			82455	10	200
		WHITE		82441	82456	10	200
		BROWN			82457	10	200

# Tamper Resistant Isolated Ground Duplex Receptacles

- 2 Pole 3 Wire
- Back & Side Wired
- Made of GE Lexan
- Steel Mounting Strap
- 4 Corner Latches Secure Face
- Washer Type Break Off Plaster Ears
- Brass Strap Self Grounding Clip
- UL 94V-2 Flame Rating
- Temperature Rating: -40°F to 167°F
- Accepts #10 to #14 Stranded or Solid CU
- Touch Proof Side Barriers
- Large Head Captive Tri-Combo Screws



AMPS	VOLTAGE	COLOR	ISOLATED GROUND	BOX QTY	CASE QTY
<b>15 AMP 125V 5-15R</b>					
15	125	IVORY	82445	10	200
		WHITE	82446	10	200
		ORANGE	82449	10	200
<b>20 AMP 125V 5-20R</b>					
20	125	IVORY	82450	10	200
		WHITE	82451	10	200
		ORANGE	82454	10	200

# Tamper & Weather Resistant Duplex Receptacles

Complies with 2011 NEC Article 406.9 that states that all receptacles installed in wet & damp locations must be weather resistant. "WR" designations provide visual identification. Weather Resistant Receptacles offer protection from rain, snow, ice, moisture, & humidity when properly installed in an approved weather protective or while-in-use cover. Combine WR receptacles with any of our While-in-Use Covers.

- 2 Pole 3 Wire
- Back & Side Wired
- Made of GE Lexan, Steel Mounting Strap
- Washer Type Break Off Plaster Ears
- Large Head Captive Tri-Combination Screws
- Green Hex-Head Ground Screw
- UL 94V-2 Flame Rating
- Temperature Rating: -40°F to 167°F
- Accepts #12 or #14 Stranded or Solid CU (Push-In #14 Solid Only)



AMPS	VOLTAGE	COLOR	COMMERCIAL GRADE	BOX QTY	CASE QTY
<b>15 AMP 125V 5-15R</b>					
15	125	IVORY	82500	10	200
		WHITE	82501	10	200
		BROWN	82502	10	200
<b>20 AMP 125V 5-20R</b>					
20	125	IVORY	82505	10	200
		WHITE	82506	10	200
		BROWN	82507	10	200