

Decorative Tamper Resistant Duplex Receptacles



- Decorative Receptacle - Tamper Resistant
- Built-In Protective Shutter Mechanism Prevents Insertion of Foreign Objects - Clearly Visible TR Marking On Face
- Back & Side Wired
- Made of GE Lexan, Zinc Plated Steel Mounting Strap
- Accepts #12 or #14 Stranded or Solid Copper (Push-In #14 Solid Only)
- Washer Type Break Off Plaster Ears
- Large head Captive Combination Screws for quick wiring
- Easy-Access Green Hex-Head Ground Screw
- UL 94V-2 Flame Rating
- Temperature Rating: -40°F to 167°F



FIG 1



FIG 2



FIG 3



FIG 4

AMPS	VOLTAGE	COLOR	RESIDENTIAL GRADE	COMMERCIAL GRADE	ISOLATED GROUND	FIGURE	BOX QTY	CASE QTY
15 AMP 125V 5-15R								
15	125	IVORY	81960	82465		1	10	200
		WHITE	81961	82466		1	10	200
		ALMOND	81963			1	10	200
20 AMP 125V 5-20R								
20	125	IVORY		82470		2	10	200
		WHITE		82471		2	10	200
15 AMP 125V 5-15R								
15	125	IVORY			82475	3	10	200
		WHITE			82476	3	10	200
		ORANGE			82479	3	10	200
20 AMP 125V 5-20R								
20	125	IVORY			82480	4	10	200
		WHITE			82481	4	10	200
		ORANGE			82484	4	10	200

USB Chargers & Tamper Resistant Decorative Receptacles

- Decorative Receptacle with USB Charging Ports Tamper Resistant
- 4 Amps - 5 VDC
- Compatible with USB 1.1/2.0/3.0 Device
- Built-In Protective Shutter Mechanism prevents Insertion Of Foreign Objects
- Clearly Visible TR Marking On Face
- Accepts #12 or #14 Stranded or Solid Copper (Push-In #10 to #14 Solid Only)
- Washer Type Break Off Plaster Ears
- Large head Captive Combination Screws
- Easy-Access Green Hex-Head Ground Screw

- Zinc Plated Steel Mounting Strap
- Back & Side Wired
- Made of GE Lexan
- UL 94 V2 Flame Rating
- Temperature Rating: -4°F to 140°F
- ETL listed



**RAPID CHARGE
4 AMP 5V DC**



FIG 1



FIG 2

AMPS	VOLTAGE	COLOR	CAT. NO.	FIGURE	BOX QTY	CASE QTY
2 USB PORTS W/ DECORATIVE RECEPTACLE						
15	125	IVORY	82370	1	10	40
		WHITE	82371	1	10	40
20	125	IVORY	82375	1	10	40
		WHITE	82376	1	10	40

WIRING DEVICES
Tamper Resistant Receptacles