



# POWER CONNECTORS

## Black Insulated Multi-Cable Connector - Single Entry



- Insulated with rugged high-dielectric rubber/vinyl coating
- Pre-filled with oxide inhibitor
- Easy re-entry for changes, inspection or troubleshooting
- Plugs marked with connector max wire size for easy identification
- 6061 aluminum dual rated for use with copper and/or aluminum wires
- One wire per terminal
- UL/CSA certified through 600MCM size



**Dual-Rated CU9AL**  
90°C 600V

Dimension Measurements = Inches

Cat No.	Wire Ports	Wire Range	Allen Hex	Dimensions		Box Qty	Each
				Length	Height		
97513	3	4-14	1/8	1.54	1.45	12	
97514	4			1.97		6	
97516	6			2.82		4	
97518	8			3.65		4	
97533	3	2/0-14	7/32	2.34	1.50	6	
97534	4			3.01		6	
97535	5			3.69		4	
97536	6			4.36		4	
97537	7			4.74		3	
97538	8			5.41		3	
97543	3	250-6	5/16	2.99	2.10	4	
97544	4			3.85		4	
97545	5			4.71		3	
97546	6			5.57		3	
97547	7			6.43		2	
97548	8			7.29		2	
97553	3	350-6	5/16	3.52	2.50	4	
97554	4			4.57		3	
97555	5			5.62		3	
97556	6			6.67		2	
97557	7			7.72		2	
97558	8			8.77		2	
97563	3	600-4	5/16	4.89	2.90	3	
97564	4			5.63		2	
97565	5			7.11		2	
97566	6			8.47		2	
97567	7			9.83		2	
97568	8			11.18		2	
97573	3	750-250	5/16	4.90	3.60	3	
97574	4			6.19		1	
97575	5			7.75		1	
97576	6			9.18		1	
97577	7			10.60		1	
97578	8			12.03		1	