



POWER CONNECTORS

Black Insulated Multi-Cable Connector - Dual Entry



- Insulated with rugged high-dielectric rubber/vinyl coating
- Pre-filled with oxide inhibitor
- Easy re-entry for changes, inspection or troubleshooting
- Plugs marked with connector max wire size for easy identification
- 6061 aluminum dual rated for use with copper and/or aluminum wires
- One wire per terminal
- UL/CSA certified through 600MCM size



Dual-Rated CU9AL
90°C 600V

Dimension Measurements = Inches

Cat No.	Wire Ports	Wire Range	Allen Hex	Dimensions Length	Dimensions Height	Box Qty	Each			
97613	3	4-14	1/8	1.54	1.45	12				
97614	4			1.97		6				
97616	6			2.82		3				
97618	8			3.65		3				
97633	3	2/0-14	7/32	2.34	1.50	6				
97634	4			3.01		6				
97635	5			3.69		4				
97636	6			4.36		4				
97637	7			5.05		3				
97638	8			5.72		3				
97639	9			6.37		1				
97640	10			7.03		1				
97641	11			7.76		1				
97642	12			8.40		1				
97643	3			250-6		5/16	2.99	2.10	4	
97644	4						3.85		4	
97645	5	4.71	3							
97646	6	5.57	3							
97647	7	6.43	2							
97648	8	7.29	2							
97649	9	8.15	1							
97650	10	9.01	1							
97651	11	9.87	1							
97652	12	10.73	1							
97653	3	350-6	5/16		3.52		2.50		4	
97654	4				4.57				3	
97655	5			5.62	3					
97656	6			6.67	2					

Cat No.	Wire Ports	Wire Range	Allen Hex	Dimensions Length	Dimensions Height	Box Qty	Each			
97657	7	350-6	5/16	7.72	2.50	2				
97658	8			8.77		2				
97659	9			9.82		1				
97660	10			10.87		1				
97661	11			11.92		1				
97662	12			12.97		1				
97663	3	600-4	5/16	4.39	2.90	3				
97664	4			5.63		2				
97665	5			7.11		2				
97666	6			8.47		2				
97667	7			9.83		2				
97668	8			11.18		2				
97669	9			12.53		1				
97670	10			13.88		1				
97671	11			15.23		1				
97672	12			16.58		1				
97673	3			750-250		5/16	4.90	3.60	3	
97674	4						6.19		1	
97675	5	7.75	1							
97676	6	9.18	1							
97677	7	10.60	1							
97678	8	12.03	1							
97679	9	13.46	1							
97680	10	14.88	1							
97681	11	16.30	1							
97682	12	17.73	1							