



POWER CONNECTORS

Insulated Mountable - Single Entry



- Isolated bolt holes for mounting to trough, panel or wireway
- Insulated with rugged high-dielectric rubber/vinyl coating
- Pre-filled with oxide inhibitor
- Plugs marked with connector max wire size for easy identification
- 6061 aluminum dual rated for use with copper and/or aluminum wires
- One wire per terminal
- CSA Certified through 600MCM size



Dual-Rated CU9AL
90°C 600V

Dimension Measurements = Inches

Cat. No.	Wire Ports	Wire Range	Allen Hex	Bolt	Dimensions		Each
					Length	Height	
97712	2	4-14	1/8	#10	1.97	1.45	
97714	4				2.82		
97716	6				3.65		
97732	2	2/0-14	7/32	#12	3.01	1.50	
97733	3				3.69		
97734	4				4.36		
97735	5				4.74		
97736	6				5.41		
97742	2	250-6	5/16	1/4	3.85	2.10	
97743	3				4.71		
97744	4				5.57		
97745	5				6.43		
97746	6				7.29		
97752	2	350-6	5/16	5/16	4.57	2.50	
97753	3				5.62		
97754	4				6.67		
97755	5				7.72		
97756	6				8.77		
97762	2	600-4	5/16	5/16	5.63	2.90	
97763	3				7.11		
97764	4				8.47		
97765	5				9.83		
97766	6				11.18		
97772	2	750-250	3/8	3/8	6.19	3.60	
97773	3				7.75		
97774	4				9.18		
97775	5				10.60		
97776	6				12.03		