



POWER CONNECTORS

Insulated Mountable - Dual Entry



- Isolated bolt holes for mounting to trough, panel or wireway
- Insulated with rugged high-dielectric rubber/vinyl coating
- Pre-filled with oxide inhibitor
- Plugs marked with connector max wire size for easy identification
- 6061 aluminum dual rated for use with copper and/or aluminum wires
- One wire per terminal
- CSA Certified through 600MCM size



Dual-Rated CU9AL
90°C 600V

Dimension Measurements = Inches

Cat No.	Wire Ports	Wire Range	Allen Hex	Bolt	Length	Height	Each
97812	2	4-14	1/8	#10	1.97	1.45	
97814	4				2.82		
97816	6				3.65		
97832	2	2/0-14	7/32	#12	3.01	1.50	
97833	3				3.69		
97834	4				4.36		
97835	5				5.05		
97836	6				5.72		
97837	7				6.37		
97838	8				7.03		
97839	9				7.76		
97840	10				8.40		
97842	2				250-6		5/16
97843	3	4.71					
97844	4	5.57					
97845	5	6.43					
97846	6	7.29					
97847	7	8.15					
97848	8	9.01					
97849	9	9.87					
97850	10	10.73					
97852	2	350-6	5/16	5/16		4.57	
97853	3				5.62		
97854	4				6.67		
97855	5				7.72		
97856	6				8.77		
97857	7				9.82		
97858	8				10.87		
97859	9				11.92		
97860	10				12.97		

Cat No.	Wire Ports	Wire Range	Allen Hex	Bolt	Length	Height	Each
97862	2	600-4	5/16	5/16	5.63	2.90	
97863	3				7.11		
97864	4				8.47		
97865	5				9.83		
97866	6				11.18		
97867	7				12.53		
97868	8				13.88		
97869	9				15.23		
97870	10				16.58		
97872	2				750-250		3/8
97873	3	7.75					
97874	4	9.18					
97875	5	10.60					
97876	6	12.03					
97877	7	13.46					
97878	8	14.88					
97879	9	16.30					
97880	10	17.73					