

2 in 1 LAN Tester & Multimeter



- Tests the correct pin configuration of 10 Base-T cable (Cat. 5), 10 Base-2 cable (coax), RJ45/RJ11 modular cables, 356A, TIA-568A/568B and Token Ring cable
- With remote kit it can test cables up to 300m away, either on wall plate or patch panel
- Verify the cable continuity, open, short, and cross connect
- Can test the ground wire
- Measures DC/AC voltage, DC/AC current, resistance, continuity, and diodes
- 9 volt & (2) AAA batteries included
- Size 162mm x 74mm x 44mm
- Weight 308g

Multimeter Specifications

Function	Max Range	Accuracy
Voltage DC	600V	±0.5%
Voltage AC	600V	±1.2%
Current DC	200mA	±1.5%
Current AC	200mA	±2.0%
Resistance	20MΩ	±0.8%
Continuity Test	Beep if less than 100Ω	

Cat No.	Each
57314	

Tone Generator & Probe



- Identifies the state in the working telephone line (clear, ring, busy) within a group

- Designed to identify and trace wires or cables without damaging insulation
- Identifies polarity of a telephone line
- Trace & identify wires in a bundle, at a cross-connect point or remote end
- Can identify split pairs when one wire from a pair has been terminated
- Used to send or trace a tone
- Use on twisted pair wiring (telecom/datacom), single conductors, coaxial cables, de-energized AC wiring, & most other wiring
- The probe identifies the signal from the tone generator through drywall, wood & other non-metallic materials
- Continuity test
- Adjustable sensitivity/volume control to increase accuracy
- Recessed On/Off button prevents battery drain.
- Send tone frequency: 1.5KHz, Receives frequency range: 100~300 KHz
- Size: receiver 9.4" x 1.7" x 1", emitter 5.7" x 1.4" x 1"
- Weight: receiver 3.7oz., emitter 4oz. • Power: 6F22(9V)x1

Cat No.	Each
57320	

Light Meter



Measures both footcandle & Lux

- Easy to use Pocket Size & Light Weight
- 3 1/2 Digit LCD Display with Low Battery Indication
- Resolution To 0.1 Lux Measurement; 1 footcandle = 10.76 lux
- Measuring Range 200, 2000, 20000, 50000 Lux
- 20000 Lux: Reading x 10, 50000 Lux: READING x 100
- Accuracy: ±5% Rdg ±10 Digits (<10,000 Lux)
- Accuracy: ±10% Rdg ±10 Digits (>10,000 Lux)
- Calibrated to Standard Incandescent Lamp 2856K
- Includes One 12 Volt Battery
- Photo Detector Dimensions: 4.5" X 2.4" X 1.1"
- Dimensions: 4.5" X 2.5" X 1.1"
- Weight: 5.6 Ounces

Cat No.	Each
59150	