

# Insulated Splices - Single Side Entry - Mountable



- ▶ Mountable
- ▶ Single Side Entry
- ▶ 6061-T6 Aluminum
- ▶ Insulated with Rugged High-Dielectric Plastisol Dipped Coating
- ▶ Pre-filled with Oxide Inhibitor
- ▶ Easy Re-Entry for Changes, Inspection or Troubleshooting
- ▶ Plugs Marked with Connector Max Wire Size for easy identification
- ▶ CU9AL Dual Rated for use with Copper and/or Aluminum Wire
- ▶ One Wire Per Terminal
- ▶ Temperature Range of -49°F to 194°F (-45° to 90°C)
- ▶ 600 Volts
- ▶ Rated For Use with 90°C Cables
- ▶ ANSI C119.4 & UL 486B listed
- ▶ Indoor Use Only



Dimensions = Inches

Cat. No.	Wire Ports	Wire Range	Allen Hex	Length	Height
97712	2			1.97	
97714	4	4-14	1/8	2.82	1.45
97716	6			3.65	
97732	2			3.01	
97733	3			3.69	
97734	4	2/0-14	7/32	4.36	1.50
97735	5			4.74	
97736	6			5.41	
97742	2			3.85	
97743	3			4.71	
97744	4	250-6	5/16	5.57	2.10
97745	5			6.43	
97746	6			7.29	
97752	2			4.57	
97753	3			5.62	
97754	4	350-6	5/16	6.67	2.50
97755	5			7.72	
97756	6			8.77	
97762	2			5.63	
97763	3			7.11	
97764	4	600-4	5/16	8.47	2.90
97765	5			9.83	
97766	6			11.18	
97772	2			6.19	
97773	3			7.75	
97774	4	750-250	3/8	9.18	3.60
97775	5			10.60	
97776	6			12.03	