

# Insulated Splices - Dual Side Entry - Mountable



- ▶ Mountable
- ▶ Dual Side Entry
- ▶ 6061-T6 Aluminum
- ▶ Insulated with Rugged High-Dielectric Plastisol Dipped Coating
- ▶ Pre-filled with Oxide Inhibitor
- ▶ Easy Re-Entry for Changes, Inspection or Troubleshooting
- ▶ Plugs Marked with Connector Max Wire Size for easy identification
- ▶ CU9AL Dual Rated for use with Copper and/or Aluminum Wire
- ▶ One Wire Per Terminal
- ▶ Temperature Range of -49°F to 194°F (-45° to 90°C)
- ▶ 600 Volts
- ▶ Rated For Use with 90°C Cables
- ▶ ANSI C119.4 & UL 486B listed

Dimensions = Inches

Cat. No.	Wire Ports	Wire Range	Allen Hex	Length	Height
97812	2			1.97	
97814	4	4-14	1/8	2.82	1.45
97816	6			3.65	
97832	2			3.01	
97833	3			3.69	
97834	4			4.36	
97835	5			5.05	
97836	6	2/0-14	7/32	5.72	1.50
97837	7			6.37	
97838	8			7.03	
97839	9			7.76	
97840	10			8.40	
97842	2			3.85	
97843	3			4.71	
97844	4			5.57	
97845	5			6.43	
97846	6	250-6	5/16	7.29	2.10
97847	7			8.15	
97848	8			9.01	
97849	9			9.87	
97850	10			10.37	
97852	2			4.57	
97853	3			5.62	
97854	4			6.67	
97855	5			7.72	
97856	6	350-6	5/16	8.77	2.50
97857	7			9.82	
97858	8			10.87	
97859	9			11.92	
97860	10			12.97	
97862	2			5.63	
97863	3			7.11	
97864	4			8.47	
97865	5			9.83	
97866	6	600-4	5/16	11.18	2.90
97867	7			12.53	
97868	8			13.88	
97869	9			15.23	
97870	10			16.58	
97872	2			6.19	
97873	3			7.75	
97874	4			9.18	
97875	5			10.60	
97876	6	750-250	3/8	12.03	3.60
97877	7			13.46	
97878	8			14.88	
97879	9			16.30	
97880	10			17.73	