

## Photocontrols - Flush Mount



Fig 1



Fig 2

- ▶ Weatherproof Polycarbonate Housing & Lens
- ▶ SPST - Normally Open
- ▶ 1/2" CDS Photocell
- ▶ 30-60 Second Time Delay
- ▶ Light Levels: ON: .9 to 1.9 FC OFF: 2.8 To 5.6 FC
- ▶ Thermal Switch
- ▶ Temperature Range: -40°F to 158°F
- ▶ Relative Humidity: 96%
- ▶ Contact position at night is normally closed
- ▶ Power Consumption Below 1.5 Watts Max
- ▶ Life Cycle: 6500 Cycles
- ▶ 3/8"-18 Thread Nipple with Rubber Gasket and Plastic Locknut
- ▶ 6" Leads Exit Rear of Housing for Tight locations
- ▶ 39069 body detached from sensor for convenient wiring



Cat. No.	Fig	Voltage	Tungsten Rating	Ballast Rating	Case Qty
39030	1	120V	1800W	1100VA	150
39032	1	208-277V	2000W	2000VA	150

### Mini-Flush Mount ( Replacement For 71299-71301 Fixtures Pg CC7)

39069	2	120V	150W	100VA	150
-------	---	------	------	-------	-----

## Flush Mount with Wallplate



- ▶ Weatherproof Polycarbonate Housing & Lens
- ▶ Brushed Aluminum Wallplate and Gasket
- ▶ SPST - Normally Open
- ▶ 1/2" CDS Photocell
- ▶ 30-60 Second Time Delay
- ▶ Light Levels: ON: .9 to 1.9 FC OFF: 2.8 To 5.6 FC
- ▶ Thermal Switch
- ▶ Temperature Range: -40°F to 158°F
- ▶ Relative Humidity: 96%
- ▶ Contact position at night is normally closed
- ▶ Power Consumption Below 1.5 Watts Average
- ▶ Life Cycle: 6500 Cycles
- ▶ 3/8"-18 Thread Nipple with Rubber Gasket and Plastic Locknut
- ▶ 6" Leads Exit Rear of Housing for Tight locations



Cat. No.	Voltage	Tungsten Rating	Ballast Rating	Case Qty
39040	120V	1800W	1100	100
39042	208-277V	2000W	2000	100

## Photocontrols - Pencil Type



Swivel Base

- ▶ Weatherproof Polycarbonate Housing & Lens
- ▶ 1/2" CDS Light Sensor with Heat Sink
- ▶ Thermal Switch
- ▶ 30-60 Second Time Delay
- ▶ Light Levels: ON: .9 to 1.9 FC OFF: 2.8 To 5.6 FC
- ▶ Contact Position: Normally Open
- ▶ SPST
- ▶ Temperature Rate: -40°F to 158°F
- ▶ Relative Humidity: 96%
- ▶ Power Consumption: 1.5 Watts Max
- ▶ Life Cycle: 6500 Cycles
- ▶ 6" Color Coded Leads
- ▶ 1/2" Swivel Base Conduit with Rubber Gasket & Zinc Locknut



Cat. No.	Voltage	Tungsten Rating	Ballast Rating	Case Qty
39060	120V	1800W	1100 VA	100
39062	208-277V	1800W	1100 VA	100

## Photocontrol Mount - Swivel Extender



Available  
January 2015

- ▶ Swivel Adaptor for Photocontrol - Extends Length of Photoeye
- ▶ Works with the following: 39010, 39012, 39020, 39022, 39060, 39062
- ▶ Polycarbonate

Cat. No.	Description	Box Qty
39063	Photocontrol Mount Swivel Extender	1