

## Copper Ground Clamps - Serrated Collar - Rigid Conduit



- ▶ For Connecting Electrical Conduit to Water Pipe, Copper Tubing & Ground Rod
- ▶ Serrated Collar and Adaptor Swings 360° for Easy Alignment
- ▶ Cast of High Strength High Conductivity Copper Alloy
- ▶ Steel Set Screws Zinc Plated for Corrosion Resistance

Dimensions = Inches

Cat. No.	Pipe Size	Hub Size	Wire Range		Dimensions		Screw Type		Box Qty
			Min	Max	Length	Height	Top	Side	
91701	1/2 - 1	1/2	10 STR	4 STR	2.17	1.95	3/16"-24 x 1.37	5/16"-18 x 1.69	10
91702	1/2 - 1	3/4	10 STR	2/0 STR	2.17	2.15	3/16"-24 x 1.37	1/4"-20 x 1.67	10
91703	1/2 - 1	1	10 STR	3/0 STR	2.24	2.32	3/16"-24 x 1.37	1/4"-20 x 1.67	10
91704	1-1/4 - 2	1/2	10 STR	4 STR	3.58	2.54	3/16"-24 x 1.37	5/16"-18 x 2.60	5
91705	1-1/4 - 2	3/4	10 STR	2/0 STR	3.58	3.68	3/16"-24 x 1.50	5/16"-18 x 2.60	5
91706	1-1/4 - 2	1	10 STR	3/0 STR	3.58	3.81	3/16"-24 x 1.50	5/16"-18 x 2.60	5
91707	2-1/2 - 4	1/2	10 STR	4 STR	5.95	4.00	3/16"-24 x 1.50	5/16"-18 x 4.23	5
91708	2-1/2 - 4	3/4	10 STR	2/0 STR	5.95	4.20	3/16"-24 x 1.50	5/16"-18 x 4.23	5
91709	2-1/2 - 4	1	10 STR	3/0 STR	5.95	4.33	3/16"-24 x 1.50	5/16"-18 x 4.23	5

## Copper Ground Clamps - Rigid Conduit Hub



- ▶ Suitable for connecting grounding conductor in rigid conduit to water pipe, ground rod and copper weld tubing
- ▶ Standard Collar and Adaptor
- ▶ Hub Swings 360° for easy alignment
- ▶ Cast of High Strength High Conductivity Copper Alloy
- ▶ Steel Set Screws are Zinc Plated for Corrosion Resistance
- ▶ UL Listed

Dimensions = Inches

Cat. No.	Pipe Range	Conduit size	Conductor		Dimensions		Top Screw Size	Side Screw Size	Box Qty
			Min	Max	Length	Width			
90601	1/2 - 1	1/2	10	2	2.24	1.52	1/4-20 x .63	1/4-20 x 1.50	10
90602	1/2 - 1	3/4	10	2	2.24	1.52	1/4-20 x .63	1/4-20 x 1.50	10
90603	1/2 - 1	1	10	2	2.24	1.52	1/4-20 x .63	1/4-20 x 1.50	10
90604	1-1/4 - 2	1/2	10	2	3.58	2.48	5/16-18 x .73	5/16-18 x 2.25	5
90605	1-1/4 - 2	3/4	10	2	3.58	2.48	5/16-18 x .73	5/16-18 x 2.25	5
90606	1-1/4 - 2	1	10	2	3.58	2.48	5/16-18 x .73	5/16-18 x 2.25	5

## Jumper Clamps



- ▶ Cast of High Strength, High Conductivity Copper Alloy
- ▶ Stainless Steel Hardware
- ▶ Make Connections between Aluminum or Galvanized Steel and Copper or Copper Bonded Steel Wires
- ▶ Bow Design Spring Action Maintains Positive Clamping Force
- ▶ Wrap-Around Design Secures Conductor

Dimensions = Inches

Cat. No.	Finish	Conductor Range		Conductor Diameter	Bolt Material	Box Qty
		Min	Max			
91922	Tin Plated	6 SOL	1/0 STR	.162 - .373	Stainless	25
91924	Un-Plated	6 SOL	1/0 STR	.162 - .373	Stainless	25