


Lay-In Lugs - Copper - Direct Burial



- ▶ Use on Electrical Equipment, Pool/Spa Equipment, Conduit Bushings, and Jumper to Multiple Conduits
- ▶ 90572 Ideal for Grounding Swimming Pools
- ▶ 90573 Ideal for Solar applications
- ▶ Lay-In Feature for Use with Continuous Ground Loops
- ▶ Cast of High Strength Copper Alloy containing 80% or more Copper
- ▶ Stainless Steel Set Screw - 1/4" X 28 Thread
- ▶ UL 467 CSA C22.2 Approved for Direct Burial in Soil & Concrete
- ▶ Direct Burial Marked on Clamp




Dimensions = Inches

Cat. No.	Type	Awg	Wire Range	Length	Width	Height	Bolt	Box Qty
90572	Dipped	4	4 - 14	1.04"	.47"	.76"	0.26"	100
90573	Tin Plated	4	4 - 14	1.04"	.47"	.76"	0.26"	100

Ground Clamps - Lay-In - Rebar



- ▶ Connect Grounding Electrode Conductor to Bare Rebar
- ▶ Rugged and Compact
- ▶ Lay-In Feature for Use with Continuous Ground Loops
- ▶ Popular for Swimming Pool/Spa, Telecommunications, Agriculture, Marine & Food Processing Applications
- ▶ Cast of High Strength High Conductivity Copper Alloy
- ▶ Stainless Steel Hardware
- ▶ UL 467 Listed for Direct Burial In Soil & Concrete
- ▶ Not for Use on Epoxy Coated Rebar



New! Available October 2015

Dimensions = Inches

Cat. No.	Rebar Size	Wire Range		Dimensions			Box Qty
		Min	Max	Length	Width	Height	
91712	3/8"	8 SOL	6 SOL	1.14"	.74"	.75"	25
91713	1/2"	8 SOL	4 STR	1.35"	.83"	.91"	25

Ground Clamps - Vice Grip Style



- ▶ For Grounding to Flat Bar with One or Two Conductors - Copper Only
- ▶ Use as Splice or Tap
- ▶ Lay-In (Side Entry) for easy installation
- ▶ V-Groove aligns Conductors
- ▶ Interlock Design for Resistance to Vibration
- ▶ Cast of High Strength High Conductivity Bronze - Excellent Heat Dissipation

Cat. No.	Conductor Range		Box Qty
	Max	Min	
	2 Conductors	2 Conductors	
91912	6 SOL	8 SOL	25
91913	4 STR	6 SOL	25
91914	2 STR	4 SOL	25
91915	2/0 STR	2 SOL	10
91916	4/0 STR	1/0 SOL	10

Intersystem Bonding Connector



- ▶ Fast & Simple Installation on Ground Conductor Below Meter
- ▶ Lay-In feature Allows Termination to Existing Main Ground Electrode without Cutting or Splicing Conductor
- ▶ Accommodates up to 4 Intersystem Bonding Conductors
- ▶ 6061-T6 Dual Rated Aluminum Connector
- ▶ Stainless Steel Flush Mount Slot Head Screws
- ▶ UV Rated Paintable Thermoplastic Cover Included
- ▶ UL 467 Listed, Meets NEC 2008 Section 250.94 Requirements



Dimensions = Inches

Cat. No.	Conductors				Screw Type	Length	Width	Height	Box Qty
	Main Ground		Low Voltage						
	Min	Max	Min	Max					
90588	6	2	14	4	Slotted	3.93	1.19	1.40	10