






- ▶ Cree CXA LEDs
- ▶ 1/2" NPT Knuckle Mount
- ▶ Isolated Driver Compartment for Optimal Thermal Management
- ▶ Corrosion Resistant Die Cast Aluminum Housing
- ▶ Superior Architectural Powder Coat Finish
- ▶ Fluted Reflector & Tempered Glass Lens
- ▶ Photo control (not included) can be installed remotely
- ▶ Voltage: 120-277VAC
- ▶ Light Pattern: 12W-23°, 30W-75°
- ▶ Operation Temperature: -40°F to 131°F
- ▶ 50,000+ Hour LED Life Expectancy
- ▶ IP54 (NEMA 3) Dust & Watertight
- ▶ cULus Listed
- ▶ 5 Year Warranty



12 Watt Bullet




30 Watt Bullet




Cat. No.	Watts	Color Temperature	Color	Delivered Lumens	CRI	Replaces Halogen	Weight (Lbs)	Case Qty
71362	12	3000K Warm White	Bronze	817	83	75W	2	6
71368	12	3000K Warm White	Green	817	83	75W	2	6
71370	12	3000K Warm White	Black	817	83	75W	2	6
71371	12	3000K Warm White	White	817	83	75W	2	6
71363	12	5000K Cool White	Bronze	814	75	75W	2	6
71364	12	5000K Cool White	Green	814	75	75W	2	6
71372	12	5000K Cool White	Black	814	75	75W	2	6
71373	12	5000K Cool White	White	814	75	75W	2	6
71365	30	3000K Warm White	Bronze	2274	83	3 X 75W	4	6
71369	30	3000K Warm White	Green	2274	83	3 X 75W	4	6
71374	30	3000K Warm White	Black	2274	83	3 X 75W	4	6
71375	30	3000K Warm White	White	2274	83	3 X 75W	4	6
71366	30	5000K Cool White	Bronze	2500	74	3 X 75W	4	6
71367	30	5000K Cool White	Green	2500	74	3 X 75W	4	6
71376	30	5000K Cool White	Black	2500	74	3 X 75W	4	6
71377	30	5000K Cool White	White	2500	74	3 X 75W	4	6

## PVC Mounting Post



- ▶ Outdoor Low Voltage/Line Voltage Lighting Applications
- ▶ Sturdy "Ground Grabber" stabilizer with teeth and ribs for maximum stability
- ▶ Rugged, Extruded Thick Wall PVC Post with Molded-in color
- ▶ 1/2" NPT thread fits standard Floodlights & Lawn Lights

## PVC Stake



- ▶ Heavy Duty PVC Stake
- ▶ Excellent Anchor for Low Voltage & Line Voltage Lighting
- ▶ 1/2" NPT thread fits standard Floodlights & Lawn Lights

Cat No.	Diameter (A)	Spike Length (B)	Case Qty
18101	3.28"	18.5"	12

Cat No.	Diameter (A)	Spike Length (B)	Case Qty
18106	2"	8-1/2"	100
18107	3"	10"	50