

## **Recessed Lighting Retrofit Kit LED Series**

3.41"

75

mimi

5 & 6"

4.11" -



- LED Retrofit Kits for Recessed Downlighting
- ► Can be installed in most 4", 5" & 6" Downlights
- ► Aluminum Housing/Trim Paintable
- ► Simple Screw-In Installation
- ► In-Line Pluggable Disconnect Included
- Guaranteed Single Bin Color Consistency with enhanced illumination uniformity
- ▶ Dimmable Down to 10%
- Compatible with most household dimmers
- ▶ Input Voltage: 120VAC
- ► Operating Temperature: 32°F to 140°F
- ▶ 50,000+ Hour LED Life Expectancy
- Wet Location Rated
- ▶ 5 year Warranty



Cat No.	Style	Size	Color Temperature	Watts	Delivered Lumens	CRI	Replaces Incandescent	Case Qty				
Smooth Style												
72604	Smooth	4"	3000K	10.5	650	90	65W	40				
72605	Smooth	4"	4000K	10.5	650	90	65W	40				
72602	Smooth	5" & 6"	3000K	14.5	1100	90	75W	30				
72603	Smooth	5"& 6"	4000K	14.5	1100	90	75W	30				
72601	Smooth	5"& 6"	5000K	14.5	1200	80	75W	30				
Baffle Style (Grooves)												
72607	Baffle	4"	3000K	10.5	650	90	65W	40				
72608	Baffle	4"	4000K	10.5	650	90	65W	40				
72609	Baffle	5" & 6"	3000K	14.5	1100	90	75W	30				
72610	Baffle	5"& 6"	4000K	14.5	1100	90	75W	30				
72611	Baffle	5"& 6"	5000K	14.5	1200	80	75W	30				

## Surface Mount Lighting Retrofit Kit LED Series






4"

Т

2.93

3 06





## Available October 2016



- Surface Mount
- Perfect for Residential and Commercial
- Driverless AC Direct Wired
- ► Can install in 4" J-Box & most 5" & 6" Downlights
- Hardwire to J-Box OR Screw-In to Recessed Can
- ► Torsion Spring & Brackets for Can Mounting
- Aluminum Housing/Trim Paintable
- In-Line Pluggable Disconnect Included
- Guaranteed Single Bin Color Consistency with enhanced illumination uniformity
- ► Dimmable Down to 10%
- Compatible with most household dimmers
- Input Voltage: 120VAC
- ► Operating Temperature: 32°F to 140°F
- ► 50,000+ Hour LED Life Expectancy
- ► Wet Location Rated
- ► 5 year Warranty

Cat. No.	Size	Color Temperature	Watts	<b>Delivered Lumens</b>	CRI	<b>Replaces Incandescent</b>	Case Qty	
72612	6"	3000K	14.5	1100	90+	75W	30	
72613	6"	4000K	14.5	1100	90+	75W	30	
72614	6"	5000K	14.5	1100	90+	75W	30	



CC23