Square Head LED Combo Exit/Emergency Light




Emergency

DD6







- Combination LED Energy Saving Exit Sign and LED Emergency Lighting Unit In One Compact Design
- ► Long Life Energy Saving LED Lamps
- Completely Self-Contained
- ► Fully Automatic Operation
- Push to Test Switch
- Automatic Low Voltage Disconnect (LVD)
- ► 120 or 277 VAC Operation
- Charge Rate/Power On LED Indicator Light
 Energy Consumption of Less than 4 Watts for Red
- letters and Less than 2 Watts for Green Letters
 ▶ Injection-Molded, UL 94 V-O Flame Retardant,
- ► High Impact, Thermoplastic Housing
- ► Fully Adjustable Glare-Free LED Lamps
- ► Heads Rotate 180°+ for Maximum Field Flexibility
- Universal Mounting Canopy for Top or Back J-box Installation & 2 Snap-fit Face Plates
- ► Field replaceable chevron directional indicators
- Integral wiring channels to facilitate installation
- 3.6 Volt 1000/1800 mAH Sealed Ni-Cad Rechargeable Maintenance-Free Battery
- ▶ Input Current: .22A 120V .10A 277V
- ▶ Input Wattage: 1.8W Standard; 2.5W Remote Capable
- Environmentally-Coated, Solid State Charger
- Damp Location Rated
- UL 924 Listed
- ▶ 5 Year Warranty

Models 73442 - 73445 have Remote Capability for up to 2 Additional LED Remote Lamp Heads

- 2 heads 3 hours operation (Base Unit)
- 3 heads 2 hours operation (Base Unit + 1 Head)
- 4 heads 1.5 hours operation (Base Unit + 2 Heads)

Cat. No.	Led Color	Housing	Lumens Per Head	Width	Depth	Height	Case Qty
High Output							
73432	Red	White	76	11.60"	1.75"	7.20"	6
73433	Red	Black	76	11.60"	1.75"	7.20"	6
73434	Green	White	76	11.60"	1.75"	7.20"	6
73435	Green	Black	76	11.60"	1.75"	7.20"	6
High Output Remote Capable (Use only LED Remote Heads)							
73442	Red	White	76	11.60"	1.75"	7.20"	6
73443	Red	Black	76	11.60"	1.75"	7.20"	6
73444	Green	White	76	11.60"	1.75"	7.20"	6
73445	Green	Black	76	11.60"	1.75"	7.20"	6