

Cold Shrink



- ▶ Submersible Rated for Cable Jacket Repair & Splicing
- ▶ Conforms to ANSI C119.1 1986
- ▶ Silicone Rubber Jacketing Material
- ▶ Durable Tear Resistant Removable Rip-Cord Core
- ▶ 1000V Rated for Primary Insulation
- ▶ UV Resistant

Dimensions = Inches

Cat. No.	Conductor	Application	Length	Voltage	Bag Qty	Case Qty
68302	#2 - 1/0	0.37 - 0.57	8	1000	1	10
68304	2/0 - 400	0.57 - 1.35	9	1000	1	10
68306	500 - 800	0.97 - 1.95	9	1000	1	10
68308	500 - 800	0.97 - 1.95	12	1000	1	10
68310	900 - 1000	1.32 - 2.65	9	1000	1	10
68312	1250 - 2000	1.63 - 3.67	9	1000	1	10

Heat Shrink End Caps



- ▶ Simple & effective method for sealing cable ends, pipe & conduit
- ▶ Superior Resistance to Weathering, Moisture Contamination, Adverse Environmental Conditions & Common Fluid/Solvents
- ▶ Adhesive Liner provides complete environmental protection & insulation
- ▶ Heat Indicating Lines
- ▶ Continuous Operating Temperature -67°F to 230°F (-55°C to 110°C)
- ▶ Rated to 1KV 194°F (90°C) continuous use
- ▶ UL486D - Shrink temperature of 248°F (120°C)
- ▶ Black Color

Dimensions = Inches

Cat. No.	Cable Range	Length	Diameter Before Shrinking	Diameter After Shrinking	Wall Thickness
68232	2-4/0	3.5	.75	.22	.08
68234	300-1000MCM	4.0	1.30	.40	.08
68236	500-1500MCM	4.5	1.50	.50	.08
68238	900-2500MCM	4.5	2.05	.75	.08
68240	2000-2500MCM	5.0	2.75	1.00	.08

Heat Shrink Cable Repair Sleeve - 3:1 Shrink Ratio



- ▶ Recommended for Above Ground Use
- ▶ A Superior Wraparound Insulation that easily installs in Repair and Splice Applications providing Excellent Insulation and Protection for Cable Jackets
- ▶ Shut Down of system Not Required for repair
- ▶ High Shrink Ratio covers even irregular shapes
- ▶ Better split resistance than competitive products
- ▶ Simple RAIL-LESS installation with clamshell design
- ▶ Thermoplastic Adhesive Liner provides complete environmental protection and insulation
- ▶ Meets ICEA and NEMA insulation thickness specification
- ▶ Continuous operating temperature: -67°F to 230°F (-55°C to 110°C)
- ▶ Shrink temperature: 248°F (120°C)
- ▶ Black Color

Dimensions = Inches

Cat. No.	Cable Range	Length	Diameter Before Shrinking	Diameter After Shrinking	Wall Thickness
68212	8-3/0	36	1.20	0.24	.08
68214	2/0-400	36	1.80	0.60	.08
68216	400-1000	36	2.70	0.95	.08
68218	1000-2000	36	3.60	1.30	.08
68220	Multiple Conductor	36	4.95	1.65	.08
68222	Multiple Conductor	36	6.75	2.50	.08