

## Wire Harness Tape



- ▶ Used for protecting, insulating, and bundling electrical wire harnesses
- ▶ High elongation & excellent conformability for wire harnesses
- ▶ 5 mil thickness

Cat. No.	Color	Size	Packaging Type	Case Qty
60280	Black	3/4" X 66Ft X 5Mil	Bulk	208

## Friction Tape



Comparable to 3M 1755

- ▶ Cloth Construction Offering good Mechanical Protection Against Abrasion and Penetration of Cable, Splices and Wire
- ▶ Overwrap electrical connections
- ▶ Used for Temporary & Binding Tape Applications
- ▶ Adhesive Compound on both sides
- ▶ 1000v/mil minimum dielectric strength
- ▶ Meets ASTM-D69, .014" thickness

Cat. No.	Color	Size	Packaging Type	Case Qty
60210	Black	3/4" X 60Ft	Cello	100
60212	Black	2" X 60Ft	Cello	50

## Rubber Splicing Tape - 600V




Comparable to 3M 2155

- ▶ Self Fusing Rubber with liner
- ▶ High quality unvulcanized rubber that will bond quickly to itself to form a solid mass of water-tight protection for electrical wires
- ▶ Primary insulation for electrical wires & cables splices of not more than 600V
- ▶ High elongation conforms to irregular shapes
- ▶ Flexible to withstand expansion and contraction
- ▶ High resistance to salt water, steam, oils, detergents, and other chemicals make it an ideal tape for pipe repair, automotive, marine, construction, etc.
- ▶ Dielectric strength 490 volts per mil, for use up to 176°F (80°C)

Cat. No.	Color	Size	Packaging Type	Case Qty
60220	Blue	3/4" x 22Ft x 30Mil	Cello	100
60222	Blue	2" x 22Ft x 30Mil	Cello	50

## High Voltage Rubber Tape - 69KV



Comparable to 3M 130C

- ▶ Liner-Less Self Bonding High Voltage 30 mil EPR rubber Insulating Tape for Insulating and Jacketing Splices through 69kv
- ▶ Can also be used for building stress cones on power cable through 35KV
- ▶ Self-bonding, Self Amalgamating High Voltage Tape, provides tight, moisture resistant insulation without loss of electrical properties when elongated - Yields a Void-Free Build Up
- ▶ Excellent Corona, Ozone, and Chemical Resistance
- ▶ Permits Quicker Application than tape with liner
- ▶ ASTM-D-4388 HH-I-553C

Cat. No.	Color	Size	Packaging Type	Case Qty
60250	Black	3/4" X 30Ft X 30Mil	Boxed	60
60252	Black	1-1/2 " X 30Ft X 30Mil	Boxed	30

## Tinned Copper Shield Tape



Comparable to 3M 24

- ▶ Tinned Copper Mesh Shielding Tape for Replacing Shield Layer in Shielded Cable Repair of High Voltage Splices & Terminations
- ▶ Highly Conformable, use to continue shielding across a splice
- ▶ Nonflammable & non-corrosive
- ▶ Compatible with cable oils, common solvents & adhesives
- ▶ Highly Conductive, Easily Soldered
- ▶ 1" Width allows for easy application and overlap for increased safety

Cat. No.	Size	Package Type	Case Qty
60260	1" X 15Ft	Boxed	40