

- ▶ Copper & Steel Crimp Sleeves for a Variety of Branch/Tap & Fixture Applications
- ▶ Fast, Permanent Crimp Splice
- ▶ Electrolytic Copper Or Zinc-Plated Steel
- ▶ UL 486C CSA C22.2 #188

Dimensions = Inches


Cat. No.	Material	Conductor Range	Sleeve Length (L)	Inside Diameter (C)	Outside Diameter (W)	Sleeve Width (D)	Bag Qty	Master Bag Qty
22080	Copper	#18 - #10	.374	.205	.241	.295	100	1,000
22081	Copper	#14 - #8	.610	.264	.309	.364	100	1,000
22082	Steel	#18 - #10	.374	.205	.241	.295	100	1,000
22083	Steel	#14 - #8	.610	.264	.309	.364	100	1,000

Crimp Sleeves  
Wire Connectors

# Pre-Insulated Crimp Connectors



G8



- ▶ Nylon Insulated Copper Crimp Sleeve
- ▶ Use in light fixtures, appliances and other electrical & OEM applications
- ▶ Holds wires firmly even amidst vibration
- ▶ Compact design fits easily into tight locations
- ▶ Flared Skirt Beveled Opening eases wire entry & protects against splayed strand
- ▶ Rugged, yet resilient insulator
- ▶ 221°F (105°C) Rated
- ▶ UL 94V-2
- ▶ 300 Volt

Dimensions = Inches

Cat. No.	Wire Range	Max Wire Combination	Min Wire Combination	A	B	C	D	E	Bag Qty	Master Bag Qty
----------	------------	----------------------	----------------------	---	---	---	---	---	---------	----------------

### Hanging Bag 25 Pack

22100	No.22 - 18 Awg	2 #20 w 1 #18	2 #22	.102	.244	.307	.244	.709	25	100
22102	No.22 - 14 Awg	1 #18 w 1 #14	2 #22	.118	.311	.374	.283	.776	25	100
22104	No.22 - 10 Awg	3 #14	2 #22 2 #18	.157	.413	.492	.378	1.004	25	100
22106	No.16 - 10 Awg	2 #16 w 1 #10	2 #16 w 1 #12	.209	.488	.575	.472	1.091	25	100

### Bagged Bulk Pack

22000	No.22 - 18 Awg	2 #20 w 1 #18	2 #22	.102	.244	.307	.244	.709	100	1,000
22002	No.22 - 14 Awg	1 #18 w 1 #14	2 #22	.118	.311	.374	.283	.776	100	1,000
22004	No.22 - 10 Awg	3 #14	2 #22 2 #18	.157	.413	.492	.378	1.004	100	1,000
22006	No.16 - 10 Awg	2 #16 w 1 #10	2 #16 w 1 #12	.209	.488	.575	.472	1.091	500	—

### High Temperature 302°F (150°C)

22007	No.22 - 14 Awg	1 #18 w 1 #14	2 #22	.118	.311	.374	.283	.776	25	100
22008	No.22 - 10 Awg	3 #14	2 #22 #18	.157	.413	.492	.378	1.004	25	100