



Nylon Insulated Double Crimp Female Disconnects



MAXIMUM ELECTRIC CURRENT:

Awg	22	20	18	16	14	12	10
Amp	3	4	7	10	15	20	24

MAXIMUM ELECTRIC RATING: 221°F(105°C) 600 Volts

INSULATION MATERIAL: Nylon

TERMINAL MATERIAL: Electro-Tin Plated Brass

DOUBLE CRIMP: Extended Copper Sleeve for Multiple Crimps

FEATURES: Serrated Barrel, Expanded Insulation



Dimensions = Inches

Cat. No.	Color	Wire Size AWG	NEMA TAB	W	F	L	B	C	D	T	Bag Qty	Master Bag Qty
11902	Red	22-16	.020 X.110	.126	.256	.772	.433	.067	.157	.012	100	1000
11904	Red	22-16	.032 X.110	.126	.256	.772	.433	.067	.157	.012	100	1000
11906	Red	22-16	.020 X.187	.197	.252	.787	.433	.067	.157	.014	100	1000
11908	Red	22-16	.032 X.187	.197	.252	.787	.433	.067	.157	.014	100	1000
11910	Red	22-16	.020 X.205	.224	.260	.768	.433	.067	.157	.014	100	1000
11912	Red	22-16	.032 X.250	.260	.287	.846	.433	.067	.157	.016	100	1000
11914	Blue	16-14	.020 X.110	.126	.256	.772	.433	.091	.197	.012	100	1000
11916	Blue	16-14	.032 X.110	.126	.256	.772	.433	.091	.197	.012	100	1000
11918	Blue	16-14	.020 X.187	.197	.252	.787	.433	.091	.197	.014	100	1000
11920	Blue	16-14	.032 X.187	.197	.252	.787	.433	.091	.197	.014	100	1000
11922	Blue	16-14	.020 X.205	.224	.228	.768	.433	.091	.197	.014	100	1000
11924	Blue	16-14	.032 X.250	.260	.295	.846	.433	.091	.197	.016	100	1000
11926	Yellow	12-10	.020 X.110	.126	.256	.866	.512	.134	.256	.014	100	1000
11928	Yellow	12-10	.032 X.110	.126	.256	.866	.512	.134	.256	.014	100	1000
11930	Yellow	12-10	.020 X.187	.197	.256	.866	.512	.134	.256	.014	100	1000
11932	Yellow	12-10	.032 X.187	.197	.256	.866	.512	.134	.256	.014	100	1000
11934	Yellow	12-10	.032 X.250	.260	.295	.925	.512	.134	.256	.016	100	1000

Terminals Disconnects

H18

Nylon Insulated Double Crimp Male Disconnects



MAXIMUM ELECTRIC CURRENT:

Awg	22	20	18	16	14	12	10
Amp	3	4	7	10	15	20	24

MAXIMUM ELECTRIC RATING: 221°F(105°C) 600 Volts

INSULATION MATERIAL: Nylon

TERMINAL MATERIAL: Electro-Tin Plated Brass

DOUBLE CRIMP: Extended Copper Sleeve for Multiple Crimps

FEATURES: Serrated Barrel, Expanded Insulation

Dimensions = Inches

Cat. No.	Color	Wire Size AWG	NEMA TAB	W	F	L	B	C	D	T	Bag Qty	Master Bag Qty
11942	Red	22-16	.020 X.110	.110	.256	.768	.433	.067	.157	.020	100	1000
11944	Red	22-16	.032 X.110	.110	.256	.768	.433	.067	.157	.016	100	1000
11946	Red	22-16	.020 X.187	.189	.256	.768	.433	.067	.157	.020	100	1000
11948	Red	22-16	.032 X.187	.189	.264	.768	.433	.067	.157	.016	100	1000
11950	Red	22-16	.032 X.250	.250	.303	.866	.433	.067	.157	.016	100	1000
11952	Blue	16-14	.020 X.187	.189	.256	.787	.433	.091	.197	.020	100	1000
11954	Blue	16-14	.032 X.187	.189	.264	.787	.433	.091	.197	.020	100	1000
11956	Blue	16-14	.032 X.250	.250	.303	.874	.433	.091	.197	.016	100	1000
11958	Yellow	12-10	.032 X.250	.250	.303	.945	.512	.134	.256	.016	100	1000