


Nylon Fully Insulated Disconnects - Male & Female



MAXIMUM ELECTRIC CURRENT:

Awg	22	20	18	16	14	12	10
Amp	3	4	7	10	15	20	24

MAXIMUM ELECTRIC RATING: 221°F(105°C) 300 Volts

INSULATION MATERIAL: Nylon

TERMINAL MATERIAL: Electro-Tin Plated Brass


FEATURES: Serrated Barrel, Expanded Insulation, Rectangular Housing Shape

(25 Pack located on Page H2)

Dimensions = Inches

Cat No.	Type	Color	Wire Size	Tab Size	W	F	L	B	C	D	T	Bag Qty	Master bag Qty
10411	Female	Red	22-16	.250 X .032	.260	.295	.866	.433	.067	.157	.032	100	1000
10412	Female	Blue	16-14	.250 X .032	.260	.295	.866	.433	.091	.177	.032	100	1000
10414	Female	Yellow	12-10	.250 X .032	.260	.295	.945	.512	.134	.248	.032	100	1000
10415	Male	Red	22-16	.250 X .032	.250	.303	.906	.433	.067	.157	.032	100	1000
10416	Male	Blue	16-14	.250 X .032	.250	.303	.945	.433	.091	.177	.032	100	1000
10418	Male	Yellow	12-10	.250 X .032	.250	.303	.984	.512	.134	.248	.032	100	1000

Nylon Fully Insulated Double Crimp Female Disconnects



MAXIMUM ELECTRIC CURRENT:

Awg	22	20	18	16	14	12	10
Amp	3	4	7	10	15	20	24

MAXIMUM ELECTRIC RATING: 221°F(105°C) 600 Volts

INSULATION MATERIAL: Nylon

TERMINAL MATERIAL: Electro-Tin Plated Brass


DOUBLE CRIMP: Extended Copper Sleeve for Multiple Crimps

FEATURES: Serrated Barrel, Expanded Insulation, Oval Housing Shape

Dimensions = Inches

Cat. No.	Color	Wire Size AWG	NEMA TAB	W	F	L	B	C	D	T	FIG.	Bag Qty	Master Bag Qty
11962	Red	22-16	.020 X.110	.126	.256	.768	.433	.067	.157	.012	1	100	1000
11964	Red	22-16	.032 X.110	.126	.256	.768	.433	.067	.157	.012	1	100	1000
11966	Red	22-16	.020 X.187	.197	.252	.795	.433	.067	.157	.014	2	100	1000
11968	Red	22-16	.032 X.187	.197	.252	.795	.433	.067	.157	.014	2	100	1000
11970	Red	22-16	.032 X.250	.260	.295	.846	.433	.067	.157	.016	1	100	1000
11972	Blue	16-14	.020 X.187	.197	.252	.795	.433	.091	.197	.014	2	100	1000
11974	Blue	16-14	.032 X.187	.197	.252	.795	.433	.091	.197	.014	2	100	1000
11976	Blue	16-14	.032 X.250	.260	.295	.846	.433	.091	.197	.016	1	100	1000
11978	Yellow	12-10	.032 X.250	.260	.295	.953	.512	.134	.256	.016	2	100	1000

Nylon Fully Insulated Double Crimp Male Disconnects



MAXIMUM ELECTRIC CURRENT:

Awg	22	20	18	16	14	12	10
Amp	3	4	7	10	15	20	24

MAXIMUM ELECTRIC RATING: 221°F(105°C) 600 Volts

INSULATION MATERIAL: Nylon

TERMINAL MATERIAL: Electro-Tin Plated Brass

DOUBLE CRIMP: Extended Copper Sleeve for Multiple Crimps

FEATURES: Serrated Barrel, Expanded Insulation, Oval Housing Shape

Dimensions = Inches

Cat. No.	Color	Wire Size AWG	NEMA TAB	W	F	L	B	C	D	T	Bag Qty	Master Bag Qty
11980	Red	22-16	.020 X.187	.250	.256	.866	.433	.067	.157	.016	100	1000
11981	Red	22-16	.032 X.187	.250	.256	.866	.433	.067	.157	.016	100	1000
11982	Red	22-16	.032 X.250	.250	.303	.945	.433	.067	.157	.016	100	1000
11983	Blue	16-14	.020 X.187	.250	.256	.866	.433	.091	.197	.016	100	1000
11985	Blue	16-14	.032 X.187	.250	.256	.866	.433	.091	.197	.016	100	1000
11984	Blue	16-14	.032 X.250	.250	.303	.945	.433	.091	.197	.016	100	1000
11986	Yellow	12-10	.032 X.250	.250	.303	1.024	.512	.134	.256	.016	100	1000