



Vinyl Insulated Bullet Disconnects



MAXIMUM ELECTRIC CURRENT:

Awg	22	20	18	16	14	12	10
Amp	3	4	7	10	15	20	24

MAXIMUM ELECTRIC RATING: 167°F(75°C) 600 Volts

INSULATION MATERIAL: Vinyl


TERMINAL MATERIAL: Electro-Tin Plated Brass

FEATURES: Serrated Barrel, Expanded Insulation

Dimensions = Inches

Cat. No.	Color	Wire Size AWG	W	F	L	B	C	D	T	Bag Qty	Master Bag Qty
12042	Red	22-16	.157	.335	.827	.394	.067	.157	.016	100	1000
12044	Blue	16-14	.157	.335	.827	.394	.091	.177	.016	100	1000
12046	Blue	16-14	.197	.335	.827	.394	.091	.177	.016	100	1000
12048	Yellow	12-10	.197	.335	.925	.512	.134	.217	.016	100	1000

Nylon Insulated Double Crimp Bullet Disconnects



MAXIMUM ELECTRIC CURRENT:

Awg	22	20	18	16	14	12	10
Amp	3	4	7	10	15	20	24

MAXIMUM ELECTRIC RATING: 221°F(105°C) 600 Volts

INSULATION MATERIAL: Nylon

TERMINAL MATERIAL: Electro-Tin Plated Brass



DOUBLE CRIMP: Extended Copper Sleeve for Multiple Crimps

FEATURES: Serrated Barrel, Expanded Insulation

Dimensions = Inches

Cat. No.	Color	Wire Size AWG	W	F	L	B	C	D	T	Bag Qty	Master Bag Qty
12052	Red	22-16	.157	.335	.866	.433	.067	.157	.016	100	1000
12054	Blue	16-14	.157	.335	.866	.433	.091	.197	.016	100	1000
12056	Blue	16-14	.197	.335	.866	.433	.091	.197	.016	100	1000
12058	Yellow	12-10	.197	.335	.925	.512	.134	.256	.016	100	1000

Nylon Fully Insulated Double Crimp Bullet Disconnects



MAXIMUM ELECTRIC CURRENT:

Awg	22	20	18	16	14	12	10
Amp	3	4	7	10	15	20	24

MAXIMUM ELECTRIC RATING: 221°F(105°C) 600 Volts

INSULATION MATERIAL: Nylon

TERMINAL MATERIAL: Electro-Tin Plated Brass

DOUBLE CRIMP: Extended Copper Sleeve for Multiple Crimps

FEATURES: Serrated Barrel, Expanded Insulation

Dimensions = Inches

Cat. No.	Color	Wire Size AWG	W	F	L	B	C	D	T	Bag Qty	Master Bag Qty
12062	Red	22-16	.157	.412	1.063	.394	.067	.157	.016	100	1000
12064	Blue	16-14	.157	.413	1.063	.394	.091	.177	.016	100	1000