


MAXIMUM ELECTRIC CURRENT:

Awg	22	20	18	16	14	12	10
Amp	9	12	17	18	30	35	50

TERMINAL MATERIAL:

Electro-Tin Plated Tubular Copper No Insulation

FEATURES: Flared Barrel

MAXIMUM ELECTRIC RATING: 221°F(105°C) 600V

COLOR CODE: N/A

Dimensions = Inches

Cat. No.	Wire Size AWG	L	W	D	C	Bag Qty	Master Bag Qty
12802	26	.236	.059	.043	.031	100	1000
12804	26	.276	.059	.043	.031	100	1000
12806	24	.236	.059	.043	.031	100	1000
12808	24	.315	.059	.043	.031	100	1000
12810	22	.236	.067	.051	.039	100	1000
12812	22	.315	.067	.051	.039	100	1000
12814	22	.394	.067	.051	.039	100	1000
12816	20	.236	.075	.059	.047	100	1000
12818	20	.315	.075	.059	.047	100	1000
12820	20	.394	.075	.059	.047	100	1000
12822	20	.472	.075	.059	.047	100	1000
12824	18	.315	.087	.067	.055	100	1000
12826	18	.394	.087	.067	.055	100	1000
12828	18	.472	.087	.067	.055	100	1000
12830	16	.276	.098	.079	.067	100	1000
12832	16	.315	.098	.079	.067	100	1000
12834	16	.394	.098	.079	.067	100	1000
12836	16	.472	.098	.079	.067	100	1000
12838	16	.591	.098	.079	.067	100	1000
12840	16	.709	.098	.079	.067	100	1000
12842	14	.276	.130	.102	.091	100	1000
12844	14	.394	.130	.102	.091	100	1000
12846	14	.472	.130	.102	.091	100	1000
12848	14	.591	.130	.102	.091	100	1000
12850	14	.709	.130	.102	.091	100	1000
12852	12	.354	.154	.126	.110	100	1000
12854	12	.472	.154	.126	.110	100	1000
12856	12	.591	.154	.126	.110	100	1000
12858	12	.709	.154	.126	.110	100	1000
12860	10	.394	.185	.154	.138	100	1000
12862	10	.472	.185	.154	.138	100	1000
12864	10	.591	.185	.154	.138	100	1000
12866	10	.709	.185	.154	.138	100	1000
12868	10	.787	.185	.154	.138	100	1000
12870	8	.472	.228	.193	.177	100	-
12872	8	.591	.228	.193	.177	100	-
12874	8	.709	.228	.193	.177	100	-
12876	8	.787	.228	.193	.177	100	-
12878	6	.472	.283	.244	.228	100	-
12880	6	.591	.283	.244	.228	100	-
12882	6	.709	.283	.244	.228	100	-
12884	6	.787	.283	.244	.228	100	-
12886	6	.984	.283	.244	.228	100	-
12888	6	1.260	.283	.244	.228	100	-
12890	4	.591	.358	.311	.295	100	-
12892	4	.709	.358	.311	.295	100	-
12894	4	.984	.358	.311	.295	100	-
12896	4	1.260	.358	.311	.295	100	-
12898	2	.709	.402	.343	.327	100	-
12900	2	.984	.402	.343	.327	100	-
12902	2	1.260	.402	.343	.327	100	-
12904	1/0	.709	.500	.429	.406	100	-
12906	1/0	.866	.500	.429	.406	100	-
12908	1/0	1.260	.500	.429	.406	100	-