



MAXIMUM ELECTRIC CURRENT:

Awg	22	20	18	16	14	12	10
Amp	9	12	17	18	30	35	50

MAXIMUM ELECTRIC RATING: 302°F(150°C) 600V

TERMINAL MATERIAL:

Electro-Tin Plated Copper - Brazed Seam

FEATURES: Serrated Barrel

Dimensions = Inches

Cat. No.	Wire Size AWG	Stud Size	d2	W	F	L	E	D	d1	T	Bag Qty	Master Bag Qty
11011	22-16	#2	.095	.217	.189	.488	.189	.134	.067	.030	100	1000
11012	22-16	#4	.126	.217	.197	.492	.189	.134	.067	.030	100	1000
11014	22-16	#6	.146	.260	.248	.567	.189	.134	.067	.030	100	1000
11016	22-16	#8	.169	.315	.276	.622	.189	.134	.067	.030	100	1000
11018	22-16	#10	.209	.315	.276	.622	.189	.134	.067	.030	100	1000
11020	22-16	1/4	.252	.457	.433	.858	.189	.134	.067	.030	100	1000
11022	22-16	5/16	.331	.457	.433	.858	.189	.134	.067	.030	100	1000
11024	22-16	3/8	.413	.535	.547	1.004	.189	.134	.067	.030	100	1000
11026	22-16	1/2	.512	.756	.630	1.197	.189	.134	.067	.030	100	1000
11028	22-16	9/16	.591	1.063	.827	1.547	.189	.134	.067	.031	100	1000
11030	22-16	5/8	.669	1.063	.827	1.547	.189	.134	.067	.031	100	1000
11032	22-16	3/4	.827	1.063	.827	1.547	.189	.134	.067	.031	100	1000
11033	16-14	#2	.087	.217	.220	.520	.189	.161	.091	.031	100	1000
11034	16-14	#4	.126	.260	.189	.504	.189	.161	.091	.031	100	1000
11036	16-14	#6	.146	.260	.248	.567	.189	.161	.091	.031	100	1000
11038	16-14	#8	.169	.335	.291	.650	.189	.161	.091	.031	100	1000
11040	16-14	#10	.209	.335	.291	.650	.189	.161	.091	.031	100	1000
11042	16-14	1/4	.252	.472	.433	.858	.189	.161	.091	.031	100	1000
11044	16-14	5/16	.331	.472	.433	.858	.189	.161	.091	.031	100	1000
11046	16-14	3/8	.413	.535	.547	1.004	.189	.161	.091	.031	100	1000
11048	16-14	1/2	.512	.756	.630	1.197	.189	.161	.091	.031	100	1000
11050	16-14	9/16	.591	1.063	.827	1.547	.189	.161	.091	.031	100	1000
11052	16-14	5/8	.669	1.063	.827	1.547	.189	.161	.091	.031	100	1000
11054	16-14	3/4	.827	1.063	.827	1.547	.189	.161	.091	.031	100	1000
11055	12-10	#4	.126	.283	.228	.610	.236	.220	.134	.039	100	1000
11056	12-10	#6	.146	.283	.240	.618	.236	.220	.134	.039	100	1000
11058	12-10	#8	.169	.283	.240	.618	.236	.220	.134	.039	100	1000
11060	12-10	#10	.209	.374	.327	.748	.236	.220	.134	.039	100	1000
11062	12-10	1/4	.252	.472	.413	.886	.236	.220	.134	.039	100	1000
11064	12-10	5/16	.331	.591	.524	1.063	.236	.220	.134	.039	100	1000
11066	12-10	3/8	.413	.591	.524	1.063	.236	.220	.134	.039	100	1000
11068	12-10	1/2	.512	.756	.630	1.244	.236	.220	.134	.039	100	1000
11070	12-10	9/16	.591	1.260	.992	1.858	.236	.220	.134	.039	100	1000
11072	12-10	5/8	.669	1.260	.992	1.858	.236	.220	.134	.039	100	1000
11071	12-10	11/16	.748	1.260	.992	1.858	.236	.220	.134	.039	100	1000
11074	12-10	3/4	.827	1.260	.992	1.858	.236	.220	.134	.039	100	1000