

Nylon Insulated Ring Terminals



MAXIMUM ELECTRIC CURRENT:

Awg	22	20	18	16	14	12	10
Amp	9	12	17	18	30	35	50


MAXIMUM ELECTRIC RATING: 221°F(105°C) 600 Volts

INSULATION MATERIAL: Nylon

TERMINAL MATERIAL:

Electro-Tin Plated Copper - Brazed Seam

FEATURES: Serrated Barrel, Expanded Insulation



Dimensions = Inches

Cat. No.	Color	Wire Size AWG	Stud Size	d2	W	F	L	E	D	d1	T	Bag Qty	Master Bag Qty
11312	Red	22-16	#4	.126	.216	.197	.728	.433	.157	.067	.030	100	1000
11314	Red	22-16	#6	.146	.260	.248	.803	.433	.157	.067	.030	100	1000
11316	Red	22-16	#8	.169	.315	.276	.858	.433	.157	.067	.030	100	1000
11318	Red	22-16	#10	.209	.315	.276	.858	.433	.157	.067	.030	100	1000
11320	Red	22-16	1/4	.252	.457	.433	1.094	.433	.157	.067	.030	100	1000
11322	Red	22-16	5/16	.331	.457	.433	1.094	.433	.157	.067	.030	100	1000
11324	Red	22-16	3/8	.413	.535	.547	1.240	.433	.157	.067	.030	100	1000
11326	Red	22-16	1/2	.512	.756	.630	1.433	.433	.157	.067	.030	100	1000
11328	Red	22-16	9/16	.591	1.063	.827	1.783	.433	.157	.067	.031	100	1000
11330	Red	22-16	5/8	.669	1.063	.827	1.783	.433	.157	.067	.031	100	1000
11332	Red	22-16	3/4	.827	1.063	.827	1.783	.433	.157	.067	.031	100	1000
11334	Blue	16-14	#4	.126	.260	.189	.740	.433	.177	.091	.031	100	1000
11336	Blue	16-14	#6	.146	.260	.248	.803	.433	.177	.091	.031	100	1000
11338	Blue	16-14	#8	.169	.335	.307	.898	.433	.177	.091	.031	100	1000
11340	Blue	16-14	#10	.209	.335	.307	.898	.433	.177	.091	.031	100	1000
11342	Blue	16-14	1/4	.252	.472	.433	1.094	.433	.177	.091	.031	100	1000
11344	Blue	16-14	5/16	.331	.472	.433	1.094	.433	.177	.091	.031	100	1000
11346	Blue	16-14	3/8	.413	.535	.547	1.240	.433	.177	.091	.031	100	1000
11348	Blue	16-14	1/2	.512	.756	.630	1.433	.433	.177	.091	.031	100	1000
11350	Blue	16-14	9/16	.591	1.063	.827	1.783	.433	.177	.091	.031	100	1000
11352	Blue	16-14	5/8	.669	1.063	.827	1.783	.433	.177	.091	.031	100	1000
11354	Blue	16-14	3/4	.827	1.063	.827	1.783	.433	.177	.091	.031	100	1000
11356	Yellow	12-10	#6	.146	.283	.240	.894	.512	.252	.134	.039	100	1000
11358	Yellow	12-10	#8	.169	.283	.240	.894	.512	.252	.134	.039	100	1000
11360	Yellow	12-10	#10	.209	.374	.329	1.024	.512	.252	.134	.039	100	1000
11362	Yellow	12-10	1/4	.252	.472	.413	1.161	.512	.252	.134	.039	100	1000
11364	Yellow	12-10	5/16	.331	.591	.524	1.339	.512	.252	.134	.039	100	1000
11366	Yellow	12-10	3/8	.413	.591	.524	1.339	.512	.252	.134	.039	100	1000
11368	Yellow	12-10	1/2	.512	.756	.630	1.520	.512	.252	.134	.039	100	1000
11370	Yellow	12-10	9/16	.591	1.260	.992	2.134	.512	.252	.134	.039	100	1000
11372	Yellow	12-10	5/8	.669	1.260	.992	2.134	.512	.252	.134	.039	100	1000
11374	Yellow	12-10	3/4	.827	1.260	.992	2.134	.512	.252	.134	.039	100	1000

Ring Terminals

H8