

# Nylon Cable Ties - Stainless Steel Pawl



- ▶ Made from UL approved Nylon 6/6
- ▶ Stainless Steel Locking Pawl Molded into Head for Higher Load Bearing & Tensile Strength Characteristics
- ▶ Bent, Ribbed & Contoured Tip for Ease of Insertion & Low Insertion Force
- ▶ Raised Central Spine of Tie Allows for both Infinite Adjustability and Increased Strength
- ▶ Normal Service Temperature Range:
  - ▶ -40°F to 185°F (-40°C to 85°C)
  - ▶ Flammability Rating: UL94 V-2
  - ▶ Packed in Sealed Plastic Bags
  - ▶ Mil Spec MIL-C-23190

## Natural - Stainless Steel Pawl

Dimensions = Inches

Cat. No.	Tensile Strength (Lbs.)	Length	Width	Max Bundle Dia.	Bag Qty
20712	40	4	.098	0.94	100
20714	40	8	.098	2.16	100
20716	60	5-1/2	.137	1.40	100
20718	60	8	.137	2.10	100
20720	60	11	.137	3.10	100
20722	88	8	.177	2.00	100
20724	88	11	.177	3.00	100
20726	88	14	.177	3.90	100
20728	175	14	.290	3.97	50

## Ultraviolet Black - Stainless Steel Pawl

Dimensions = Inches

Cat. No.	Tensile Strength (Lbs.)	Length	Width	Max Bundle Dia.	Bag Qty
20732	40	4	.098	0.94	100
20734	40	8	.098	2.16	100
20736	60	5-1/2	.137	1.40	100
20738	60	8	.137	2.10	100
20740	60	11	.137	3.10	100
20742	88	8	.177	2.00	100
20744	88	11	.177	3.00	100
20746	88	14	.177	3.90	100
20748	175	14	.290	3.97	50

## Stainless Steel Ties



- ▶ Made of 304 Stainless Steel
- ▶ Ideally Suited for Hazardous Environments & Heavy Loads
- ▶ Roller-Ball design allows Low Insertion Force
- ▶ Self Locking for fast and easy installation
- ▶ Smooth Rounded Edges will not damage wires
- ▶ Can install by hand or with tool
- ▶ Normal Operating Temperature:
  - ▶ -112°F to 1000°F (-80°C to 538°C)
  - ▶ Non-Magnetic, UV resistant & fireproof

Dimensions = Inches

Cat. No.	Tensile Strength (Lbs.)	Length	Width	Thickness	Maximum Bundle Diameter	Bag Qty	Master Bag Qty
20912	200	5.0	.18	.01	1.0	100	1000
20914	200	7.9	.18	.01	2.0	100	1000
20916	200	10.5	.18	.01	2.7	100	1000
20918	200	14.2	.18	.01	4.0	100	1000
20920	200	20.4	.18	.01	6.0	100	-
20922	200	26.8	.18	.01	8.0	100	-
20924	200	33.0	.18	.01	10.0	100	-
20930	350	6.0	.31	.01	1.0	100	1000
20932	350	7.9	.31	.01	2.0	100	1000
20934	350	10.5	.31	.01	2.7	100	1000
20936	350	14.2	.31	.01	4.0	100	1000
20938	350	20.4	.31	.01	6.0	100	-
20940	350	26.8	.31	.01	8.0	100	-
20942	350	33.0	.31	.01	10.0	100	-